




## B300 GROEN


Customer: PTRHTF10078	System Information	Sample Information
WEST FORK CREATIONS 15 PEPSI DRIVE RED LODGE, MT 59068 USA Attn: Sean Keeney Tel: (406)426-3060 E-Mail: foodsafety@kingscupboard.com	System Volume: 70 gal Bulk Operating Temp: 475F / 246C Heating Source: Blanket: Fluid: PETRO CANADA PURITY FG HEAT TRANSFER FLUID Make: STERLCO	Lab No: 02306726 Analyst: Ron LeBlanc Sample Date: 08/22/19 Received Date: 09/06/19 Completed: 09/09/19

Recommendation: Acid number is elevated. COC Flash Point is rising back to normal. Pentane insoluble stayed about the same as previous sample. Take another sample in 3 months.

Comments: Pentane Insolubles levels are severely high. Acid Number (AN) is abnormally high.




Sample Date	Received Date	Fluid Age	Sample Location	Flash Point (COC)	Water (KF)	Viscosity (40°C)	Acid Number	Solids	GCD 10%	GCD 50%	GCD 90%	GCD % < 335°C
	mm/dd/yy			°F/°C	ppm	cSt	mg/KOH/g	%wt	°F/°C	°F/°C	°F/°C	%
08/22/19	09/06/19	6m	DRAIN	415 / 213	64.5	32.7	1.54	0.597	685 / 363	801 / 427	900 / 482	5.18
07/22/19	08/01/19	0m	DRAIN VALVE	342 / 172	74.5	32.4	0.920	0.618	664 / 351	792 / 422	895 / 480	7.11
06/28/18	07/23/18	5m	OIL DRAIN	381 / 194	23.7	31.6	1.02	0.316	685 / 363	800 / 427	899 / 482	5.01
08/15/17	08/25/17	12m		349 / 176	54.9	31.7	0.837	0.559	692 / 367	805 / 430	903 / 484	4.34
05/31/16	06/09/16	10m	DRAIN PLUG	388 / 198	21.5	33.2	0.40	0.107	705 / 374	809 / 431	901 / 483	2.90
06/30/14	07/09/14	8m	DRAIN PLUG	442 / 228	95.0	38.4	0.53	1.53	701 / 372	806 / 430	908 / 487	2.57
Baseline Data				459 / 237		37.12	0.90		721 / 383	807 / 431	892 / 478	1.5





Sample Date	Iron	Chromium	Nickel	Aluminum	Copper	Lead	Tin	Cadmium	Silver	Vanadium	Silicon	Sodium	Potassium	Titanium	Molybdenum	Antimony	Manganese	Lithium	Boron	Magnesium	Calcium	Barium	Phosphorus	Zinc
08/22/19	1	0	0	0	0	0	0	0	0	0	4	0	6	0	0	0	0	0	0	0	0	0	161	0
07/22/19	2	0	0	0	0	0	0	0	0	0	4	0	7	0	0	0	0	0	0	0	0	0	159	0
06/28/18	2	0	0	0	0	0	0	0	0	0	6	0	6	0	0	0	0	0	0	0	0	0	140	0
08/15/17	4	0	0	0	0	0	0	0	0	0	14	2	13	0	0	0	0	0	0	0	0	0	141	0
05/31/16	0	0	0	0	0	0	0	0	0	0	29	0	4	0	0	0	0	0	0	0	0	0	136	0
06/30/14	44	0	0	0	1	0	0	0	0	0	2	0	0	0	0	0	0	0	0	4	0	0	171	3
Baseline Data			0	0						0			0	0					0				230	

Elemental analysis results (above) in parts per million (ppm). [10,000 ppm = 1.0%]



Historical Comments	
07/22/19	COC Flash Point is severely low. Pentane insoluble has risen in last 3 samples. Possible process leak? Be sure to purge the system before taking sample. Re sample and check results. Oil could have been heated too high or too quickly if shut down and started back up. Add new oil to bring COC Flash Point back up. Pentane Insolubles levels are severely high. COC Flash Point is severely low. (GCD) 10% Distillation Point is marginally low.
06/28/18	COC Flash Point has come up since previous sample. Pentane Insolubles have dropped significantly from previous sample. Purge more oil out of sample port before taking next sample. COC Flash Point is marginally low.
08/15/17	Sample appears to contain water. COC flash point is slightly low. Make sure quality sample was taken properly. Allow oil to flow freely for short time before capturing in container. Take another sample to confirm results. Pentane Insolubles levels are abnormally high. COC Flash Point is severely low.
05/31/16	Overall, the sample appears to be in good condition. The flash point is slightly low which indicates that the product has some minor thermal degradation occurring. We will monitor this further on the next sample. There is also an elevated level of Silicon which can indicate contamination in your system, or possibly this was picked up during the sampling process. We will monitor this in future samples as well. Please re-sample in 6 months time. Silicon ppm levels are abnormally high. COC Flash Point is marginally low.
06/30/14	The solids have risen but the other oil properties tested appear to be acceptable even after 8 years. If the solids are creating production issues we suggest to perhaps find a way to filter them or consider an oil replacement. Pentane Insolubles levels are severely high.

Petro-Canada makes no representation or warranty of any kind, either express or implied, as to the accuracy or completeness of the analysis and assumes no responsibility and shall have no liability whatsoever with respect to such analysis, or a party's use of it. Petro-Canada is a division of HollyFrontier Corporation.