



PRESSE 3

Customer: PTRHTF30007
 COMMONWEALTH PLYWOOD
 ROUTE 117
 STE-THERESE, QC J7E 4H9 CANADA
 Attn: Carl Desforges
 Tel: (450)821-3197
 E-Mail: desforgesCarl@commonwealthplywood.com

System Information
 System Volume: 4000 ltr
 Bulk Operating Temp: 203F / 95C
 Heating Source:
 Blanket:
 Fluid: PETRO CANADA PETRO-THERM
 Make: CLEVER BROOK

Sample Information
 Lab No: 02461911
 Analyst: Luc Leblanc
 Sample Date: 11/15/21
 Received Date: 12/14/21
 Completed: 12/16/21
 Luc Leblanc
 luc.leblanc@hollyfrontier.com

Recommendation: Tous les paramètres de votre fluide Petro-Therm sont normaux. Nous recommandons d'échantillonner à votre fréquence normale.

Comments: Tous les métaux d'usure sont normaux. Il n'y a pas d'évidence de contamination. Les données GDC 10%, 50% et 90% sont normales. Le fluide Petro-Therm est en bon état et peut demeurer en service jusqu'au prochain échantillonnage.

Sample Date	Received Date	Fluid Age	Sample Location	Flash Point (COC)	Water (KF)	Viscosity (40°C)	Acid Number	Solids	GCD 10%	GCD 50%	GCD 90%	GCD % < 335°C
	mm/dd/yy			°F/°C	ppm	cSt	mg/KOH/g	%wt	°F/°C	°F/°C	°F/°C	%
11/15/21	12/14/21	3.0m		428 / 220	10.1	31.6	0.02	0.045	698 / 370	799 / 426	906 / 486	3.38
Baseline Data				433 / 223		34.2	0.03		720 / 382	817 / 436	900 / 482	1.00



