

CARGILL MEAT (THAILAND) SARABURI

Customer: PTRHTF60010

SYNLUBE INTERNATIONAL CO LTD 76/1 MOO.7 THACHIN

MUANG SAMUTSAKHON, 74000 TH

Attn: CHERNPORN CHOBKUI

Tel: 034421290

E-Mail: chernporn@synlube.co.th

System Information

System Volume: 10000 ltr

Bulk Operating Temp: 554F / 290C

Heating Source:

Blanket:

Fluid: PETRO CANADA PURITY FG HEAT TRANSFER FLUID

Make: WANSON

Sample Information

Lab No: 02574687 Analyst: Philip Riley Sample Date: 07/20/23 Received Date: 08/08/23 Completed: 09/11/23


Philip Riley

philip.riley@HFSinclair.com

Recommendation: Whilst flash point is marginally low, it remains at an acceptable level. Distillation being slightly high also (90%) which indicates some form of cracking producing light ends and heavy molecules. Oil is fit for further use, please re sample at normal frequency

Comments: (GCD) 90% Distillation Point is marginally high. COC Flash Point is marginally low.





Petro-Canada makes no representation or warranty of any kind, either express or implied, as to the accuracy or completeness of the analysis and assumes no responsibility and shall have no liability whatsoever with respect to such analysis, or a party's use of it. Petro-Canada is a division of HollyFrontier Corporation.