# LIEBHERR

## **CONSTRUCTION EQUIPMENT**

## 102383 - Diesel Engine

Sample No: LH0202375

Oil Type: PETRO CANADA SUPREME 5W30



OIL CO	<b>ONDITION</b>			
Visc @ 100°C	cSt	<b>13.1</b>	 	
Oxidation (PA)	%	59	 	

CONTAMINATION					
Soot %	%	<b>0</b> 0			
Nitration (PA)	%	63			
Sulfation (PA)	%	53			
Glycol	%	NEG			
Fuel	%	<1.0			
Silicon	ppm	<b>6</b>			
Sodium	ppm	<b>2</b>			
Potassium	ppm	<b>1</b>			

WEAI	RMETALS			
Iron	ppm	<b>3</b>	 	
Copper	ppm	<b>1</b>	 	
Lead	ppm	<b>()</b> <1	 	
Tin	ppm	<b>0</b> <1	 	
Aluminum	ppm	<b>1</b>	 	
Chromium	ppm	<b>0</b> <1	 	
Molybdenum	ppm	<b>50</b>	 	
Nickel	ppm	<b>0</b> <1	 	
Titanium	ppm	0	 	
Silver	ppm	<1	 	
Manganese	ppm	<b>0</b> <1	 	
Vanadium	ppm	0	 	

ADDITIVES						
Calcium	ppm	<b>1197</b>				
Magnesium	ppm	<b>864</b>				
Zinc	ppm	<b>1201</b>				
Phosphorus	ppm	<b>1040</b>				
Barium	ppm	<b>0</b>				
Boron	ppm	<b>11</b>				

Report Id: AMEHAM [WCAMIS] 02450669 (Generated: 10/03/2023 11:46:47) Rev: 1





#### **American Iron and Metal**

75 Steel City Court Hamilton, ON CA L8H 3Y2

Contact: Heavy Equipment

hamiltonmobileassetmaintenance@aim-recycling.com

T: (905)547-5533 F: (905)544-5671

### Diagnosis

Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:AMEHAMUnique No:5294204Signed:Wes DavisReport Date:18 Oct 2021

# LIEBHERR

CONSTRUCTION EQUIPMENT





### **GRAPHS**

