

[RONI] 360 - Hydraulic System

Sample No: LH

Oil Type: {unknown}

SAMPLE INFORMATION

Sample Number		LH	LH0232551				
Sample Date		04 Jun 2023	09 Mar 2023				
Machine Hours		8864	1000				
Oil Hours		0	0				
Oil Changed		N/A	Not Changd				
Sample Status		SEVERE	SEVERE				
OIL CONDITION							
Visc @ 40°C	cSt	42.1	42.2				

CONTAMINATION Water % NEG NEG 63466 Particles >4µm 51140 0 4554 0 3143 Particles >6µm Particles >14µm 0 99 0 24 ISO 4406:1999 (c) 23/19/14 23/19/12 Silicon 07 $\bigcirc 7$ ppm Sodium ppm ○ <1 $\bigcirc 2$ Potassium 01 ppm ○ <1

WEAR METALS

Iron	ppm	0 15	0 15	
Copper	ppm	0 17	0 17	
Lead	ppm	02	2	
Tin	ppm	0	○ <1	
Aluminum	ppm	3	3	
Chromium	ppm	○ <1	○ <1	
Molybdenum	ppm	18	0 18	
Nickel	ppm	○ <1	○ <1	
Titanium	ppm	0	<1	
Silver	ppm	0	0	
Manganese	ppm	<1	○ <1	
Vanadium	ppm	0	0	

Q

Calcium	ppm	2361	2396				
Magnesium	ppm	12	0 11				
Zinc	ppm	776	755				
Phosphorus	ppm	716	697				
Barium	ppm	0	0				
Boron	ppm	3	03				





RONI/IRON SHORE EXCAVATING LTD. 100 MACINTOSH BLVD VAUGHAN, ON CA L4K 4P3 Context: Service Team

Contact: Service Team service.team@roni.ca T: F:

Diagnosis

Check seals and/or filters for points of contaminant entry. The air breather requires service. If unrated, we recommend that you replace with a suitable micron rated and/or desiccant air breather. If rated, we recommend that you service/replace the breather. We recommend you service the filters on this component. Resample in 30-45 days to monitor this situation. Please specify the brand, type, and viscosity of the oil on your next sample.All component wear rates are normal. There is a high amount of silt (particulates < 14 microns in size) present in the oil. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:RONVAUUnique No:5590837Signed:Wes DavisReport Date:06 Jun 2023

Report Id: RONVAU [WCAMIS] 02561796 (Generated: 01/11/2024 14:15:48) Rev: 1

Contact/Location: Service Team - RONVAU

LEBHERR CONSTRUCTION EQUIPMENT



GRAPHS

 \bigcirc

