LIEBHERR

CONSTRUCTION EQUIPMENT



Sample No: LH0260930

Oil Type: GEAR OIL SAE 80W90

_						
SAMPLEINFORMATION						
Sample Number	LH0260930					
Sample Date	29 Jun 2023					
Machine Hours	1144					
Oil Hours	0					
Oil Changed	N/A					
Sample Status	NORMAL					

Campic	Otatas		HOHIWAL		
	OIL CO	NDITION			
Visc @	40°C	cSt	196	 	

CONT	AMINATIO	ON		
Silicon	ppm	273	 	
Sodium	ppm	16	 	
Potassium	ppm	29	 	

WEA	R METALS			
Iron	ppm	282	 	
Copper	ppm	○ <1	 	
Lead	ppm	0	 	
Tin	ppm	0	 	
Aluminum	ppm	82	 	
Chromium	ppm	4	 	
Molybdenum	ppm	○ <1	 	
Nickel	ppm	2	 	
Titanium	ppm	5	 	
Silver	ppm	0	 	
Manganese	ppm	4	 	
Vanadium	ppm	<1	 	

ADDITIVES						
Calcium	ppm	124				
Magnesium	ppm	26				
Zinc	ppm	8				
Phosphorus	ppm	2260				
Barium	ppm	3				
Boron	ppm	2				



10 CHEMIN DU PETIT BERNIER ST-JEAN-SUR-RICHELIEU, QC CA J3B 678

Contact: Service Manager

T: F:

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:PYR10STJUnique No:5604657Signed:Kevin MarsonReport Date:30 Jun 2023







GRAPHS

