LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH30M 145455-1253 - Swing Drive

Sample No: LH0270068

Oil Type: LIEBHERR GEAR BASIC 90 LS



sample	Status		NORMAL	 	
	OIL CO	NDITION			
/isc @	40°C	cSt	175	 	

CONTAMINATION						
Silicon	ppm	4				
Sodium	ppm	6				
Potassium	ppm	1				

WEA	R METAL	S		
Iron	ppm	89	 	
Copper	ppm	40	 	
Lead	ppm	2	 	
Tin	ppm	3	 	
Aluminum	ppm	1	 	
Chromium	ppm	() <1	 	
Molybdenum	ppm	0	 	
Nickel	ppm	0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	2	 	
Vanadium	ppm	0	 	

ADDITIVES						
Calcium	ppm	28				
Magnesium	ppm	1				
Zinc	ppm	68				
Phosphorus	ppm	2241				
Barium	ppm	11				
Boron	ppm	7				



METAL EXPRESS (9055-2480 QUEBEC INC) 254 RUE RICHARD-AUDET ROXTON FALLS, QC CA J0H 1E0 Contact: Service Manager

T: (450)522-5650

F:

Diagnosis

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.Les taux d'usure de tous les composants sont normaux. Il n'y a aucun indice de contamination dans l'huile. L'état de l'huile est acceptable pour la durée de service.

Depot:METROXUnique No:5607261Signed:Wes DavisReport Date:14 Jul 2023

LIEBHERR





GRAPHS

