LIEBHERR

CONSTRUCTION EQUIPMENT

[HAMMERSTONE] 16012 - Diesel Engine

Sample No: LH0265037

Oil Type: DIESEL ENGINE OIL SAE 40



OILC	ONDIT	ION		
Visc @ 100°C	cSt	13.9	 	
Oxidation (PA)	%	98	 	

CONTAMINATION					
Soot %	%	0 0			
Nitration (PA)	%	116			
Sulfation (PA)	%	107			
Glycol	%	NEG		***	
Fuel	%	<1.0			
Silicon	ppm	6			
Sodium	ppm	3			
Potassium	ppm	0 <1			

WEA	R METALS			
Iron	ppm	18	 	
Copper	ppm	○ <1	 	
Lead	ppm	0	 	
Tin	ppm	0	 	
Aluminum	ppm	3	 	
Chromium	ppm	() <1	 	
Molybdenum	ppm	1	 	
Nickel	ppm	0 <1	 ***	
Titanium	ppm	() <1	 	
Silver	ppm	0	 	
Manganese	ppm	() <1	 	
Vanadium	ppm	0	 	

	pp			
ADD	DITIVES			
- ADL	HIIVES			
Calcium	ppm	2220	 	
Magnesium	ppm	19	 	
Zinc	ppm	1119	 	
Phosphorus	ppm	1010	 	
Barium	ppm	0	 	
Boron	ppm	4	 	



Liebherr-Canada Ltd.

Fort McKay Industrial Park, Lot No. 12 and 13 Fort McMurray, AB CA T9H 5N3 Contact: Corey Ekroth corey.ekroth@liebherr.com T: (780)791-2967 F:

١.

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 40. Please confirm.All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: LIEFTM
Unique No: 5607372
Signed: Kevin Marson
Report Date: 19 Jul 2023

LIEBHERR





GRAPHS

