LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH60M 142743-1217 - Diesel Engine

Sample No: LH0249559

Oil Type: DIESEL ENGINE OIL SAE 10W30

5							
SAME	PLE INFOR	MATION					
Sample Number		LH0249559	LH0249556				
Sample Date		12 Jul 2023	13 Apr 2023				
Machine Hours		1065	530				
Oil Hours		0	0				
Oil Changed		Changed	Changed				
Sample Status		NORMAL					
OIL CONDITION							
Visc @ 100°C	cSt	12.1	O 11.6				
Oxidation (PA)	%	85	201				
هـــــــــــــــــــــــــــــــــــــ							
CONTAMINATION							
Soot %	%	0 0	00				
Nitration (PA)	%	74	108				
Sulfation (PA)	%	62	109				
Glycol	%	NEG	NEG				
Fuel	%	<1.0	<1.0				
Silicon	ppm	6	O 10				
Sodium	ppm	2	3				
Potassium	ppm	() <1	3				

1 Otaooiaiii	PPIII	<u> </u>						
WEAR METALS								
Iron	ppm	6	O 11					
Copper	ppm	62	○ 265					
Lead	ppm	3	O 11					
Tin	ppm	○ <1	O 1					
Aluminum	ppm	1	3					
Chromium	ppm	○ <1	O <1					
Molybdenum	ppm	54	41					
Nickel	ppm	0	O <1					
Titanium	ppm	0	O <1					
Silver	ppm	0	O 0					
Manganese	ppm	<1	O 1					
Vanadium	ppm	0	0					

ADDITIVES								
Calcium	ppm	1039	O 1341					
Magnesium	ppm	933	O 908					
Zinc	ppm	1058	O 824					
Phosphorus	ppm	893	O 728					
Barium	ppm	6	4 0					
Boron	ppm	7	O 76					



RICHMOND STEEL RECYCLING

11760 MITCHELL ROAD RICHMOND, BC CA V6V 1V8

Contact: Aaron Kaetler AKaetler@richmondsteel.ca

T:

F: (604)324-8617

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:RIC117RICUnique No:5617179Signed:Wes DavisReport Date:26 Jul 2023

LIEBHERR

CONSTRUCTION EQUIPMENT





GRAPHS

