CONSTRUCTION EQUIPMENT

LIEBHERR LH50M 142304-1216 - Transmission

Sample No: LH

SAE 10W40 Oil Type:

SAMPLEINFORMATION						
Sample Number	LH					
Sample Date	25 Jul 2023					
Machine Hours	3000					
Oil Hours	0					
Oil Changed	Changed					
Sample Status	NORMAL					
OIL CONDITION						

OIL CO	NDITION			
Visc @ 40°C	cSt	46.5	 	

CONT	AMINATIO	ON		
Silicon	ppm	5	 	
Sodium	ppm	6	 	
Potassium	ppm	0	 	

WEA	AR META	LS		
Iron	ppm	31	 	
Copper	ppm	12	 	
Lead	ppm	() <1	 	
Tin	ppm	() <1	 	
Aluminum	ppm	4	 	
Chromium	ppm	() <1	 	
Molybdenum	ppm	58	 	
Nickel	ppm	0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	4	 	
Vanadium	ppm	0	 	

ADDITIVES						
Calcium	ppm	1166				
Magnesium	ppm	974				
Zinc	ppm	1197				
Phosphorus	ppm	1167				
Barium	ppm	0				
Boron	ppm	59				



PRODUITS FORESTIERS D.G. LTEE 313 RANG ST-JOSEPH STE-AURELIE, QC CA G0M 1M0 Contact: Roger.

T: (418)593-3547 F: (418)593-3633

Diagnosis

Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the fluid. Viscosity of sample indicates oil is within SAE 10W range, advise investigate. The condition of the fluid is acceptable for the time in service.

Depot: PRO9STE **Unique No:** 5618052 Signed: Kevin Marson **Report Date:** 31 Jul 2023

LIEBHERR







GRAPHS

