## LIEBHERR

## **CONSTRUCTION EQUIPMENT**

### LIEBHERR LH30M 136518-1253 - Diesel Engine

Sample No: LH0228849

Glycol

Silicon

Sodium

Potassium

%

ppm

ppm

ppm

Fuel

Oil Type: PETRO CANADA DURON UHP E6 10W40

**NEG** 

<1.0

**6** 

**1** 

0<1

_							
U SAM	PLE INFO	RMATION					
Sample Number		LH0228849	LH0228840	LH0228837			
Sample Date		24 Mar 2023	16 Nov 2022	09 Sep 2022			
Machine Hours		1500	1000	500			
Oil Hours		0	0	0			
Oil Changed		Changed	Changed	Changed			
Sample Status		NORMAL	NORMAL	NORMAL			
OILC	ONDITIO	N					
Visc @ 100°C	cSt	<b>13.2</b>	12.9	<b>12.0</b>			
Oxidation (PA)	%	62	83	208			
ada .							
CONTAMINATION							
Soot %	%	<b>0</b>	0	0			
Nitration (PA)	%	63	65	103			
Sulfation (PA)	%	54	64	114			

	PP							
WEAR METALS								
Iron	ppm	<b>4</b>	O 5	O 11				
Copper	ppm	<b>13</b>	O 71	<b>180</b>				
Lead	ppm	<b>0</b> <1	O 2	<b>8</b>				
Tin	ppm	<b>0</b> <1	O <1	<b>1</b>				
Aluminum	ppm	<b>1</b>	<b>1</b>	○ 3				
Chromium	ppm	<b>()</b> <1	O 0	<b>1</b>				
Molybdenum	ppm	<b>57</b>	<b>56</b>	<b>45</b>				
Nickel	ppm	<b>0</b>	O 0	O 0				
Titanium	ppm	0	<1	<1				
Silver	ppm	<b>0</b>	O 0	O 0				
Manganese	ppm	<b>()</b> <1	O <1	O 2				
Vanadium	ppm	0	0	0				

<1.0

0.9

O 12

02

ADDITIVES						
Calcium	ppm	<b>1044</b>	O 1102	1343		
Magnesium	ppm	<b>983</b>	948	○ 897		
Zinc	ppm	<b>1184</b>	O 1124	O 815		
Phosphorus	ppm	<b>1049</b>	O 1023	O 723		
Barium	ppm	<b></b> <1	<b>3</b>	32		
Boron	ppm	<b>2</b>	<b>10</b>	94		



#### CAC ENTERPRISES GROUP INC.

2411 76th AVE EDMONTON, AB CA T6P 1P6

Contact: Melody Cui

melody.cui@cacindustrials.com

F:

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:CAC241EDMUnique No:5620665Signed:Wes DavisReport Date:14 Aug 2023

# LIEBHERR

CONSTRUCTION EQUIPMENT





#### **GRAPHS**

