## LIEBHERR

**CONSTRUCTION EQUIPMENT** 

### LIEBHERR LH30M 137424-1253 - Rear Right Wheel Hub

Sample No: LH0228740

Oil Type: LIEBHERR GEAR BASIC 90 LS

_				
U SAM	PLE INF	ORMATION		
Sample Number		LH0228740	LH0228728	 
Sample Date		21 Jun 2023	10 Mar 2023	 
Machine Hours		2000	1000	 
Oil Hours		0	0	 
Oil Changed		Changed	Changed	 
Sample Status		NORMAL	NORMAL	 
OIL	ONDITION	ON		
Visc @ 40°C	cSt	63.9	67.5	 
CON	TAMIN/	ATION		
Silicon	ppm	<b>8</b>	O 7	 
Sodium	ppm	<b>14</b>	O 14	 
Potassium	ppm	<b>2</b>	O 2	 
WEA	R META	LS		
Iron	ppm	<b>17</b>	O 14	 
Copper	ppm	<b>10</b>	O 7	 
Lead	ppm	<b>0</b>	0	 

WEA	R MIE I ALS			
Iron	ppm	<b>17</b>	O 14	 
Copper	ppm	<b>10</b>	O 7	 
Lead	ppm	<b>0</b>	0	 
Tin	ppm	0	0	 
Aluminum	ppm	<b>1</b>	O <1	 
Chromium	ppm	<b>0</b> <1	O <1	 
Molybdenum	ppm	<b>0</b>	0	 
Nickel	ppm	<b>O</b> <1	0	 
Titanium	ppm	0	<1	 
Silver	ppm	<1	0	 
Manganese	ppm	<b>2</b>	O 2	 
Vanadium	ppm	0	0	 
100				

ADD ADD	ITIVES			
Calcium	ppm	3563	3659	 
Magnesium	ppm	<b>10</b>	O 10	 
Zinc	ppm	1417	1402	 
Phosphorus	ppm	1211	1223	 
Barium	ppm	<b>○</b> <1	O <1	 
Boron	ppm	106	102	 



#### CAC ENTERPRISES GROUP INC.

2411 76th AVE EDMONTON, AB CA T6P 1P6

Contact: Melody Cui

melody.cui@cacindustrials.com

T: F:

#### Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill.

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Viscosity of sample indicates oil is within SAE 80 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The condition of the oil is acceptable for the time in service.

Depot:CAC241EDMUnique No:5620808Signed:Kevin MarsonReport Date:14 Aug 2023

# LIEBHERR

### CONSTRUCTION EQUIPMENT





#### **GRAPHS**

