## LIEBHERR

**CONSTRUCTION EQUIPMENT** 

### **LIEBHERR L580 067666-1760 - Diesel Engine**

Sample No: LH0176029

Oil Type: PETRO CANADA 10W40



OILC	ONDITION			
Visc @ 100°C	cSt	<b>13.1</b>	11.3	 
Oxidation (PA)	%	55	83	 

CONTAMINATION					
Soot %	%	<b>0</b> 0	<b>0</b>		
Nitration (PA)	%	51	62		
Sulfation (PA)	%	53	65		
Glycol	%	NEG	NEG		
Fuel	%	<1.0	0.9		
Silicon	ppm	<b>6</b>	O 6		
Sodium	ppm	<b>2</b>	O 2		
Potassium	ppm	<b>0</b> <1	0 <1		

WEA	R METAL	.S		
Iron	ppm	<b>4</b>	<b>6</b>	 
Copper	ppm	<b>7</b>	○ 23	 
Lead	ppm	<b></b> <1	O 1	 
Tin	ppm	<b></b> <1	O <1	 
Aluminum	ppm	<b></b> <1	O 1	 
Chromium	ppm	<b>○</b> <1	O <1	 
Molybdenum	ppm	<b>57</b>	<b>5</b> 4	 
Nickel	ppm	<b>0</b>	0	 
Titanium	ppm	<1	<1	 
Silver	ppm	<b>0</b>	0	 
Manganese	ppm	<1	O <1	 
Vanadium	ppm	0	0	 

ADDITIVES					
Calcium	ppm	<b>1072</b>	O 1115		
Magnesium	ppm	<b>979</b>	926		
Zinc	ppm	<b>1185</b>	O 1111		
Phosphorus	ppm	<b>1044</b>	993		
Barium	ppm	<b>1</b>	<b>4</b>		
Boron	ppm	<b>2</b>	O 10		



#### WEST CARLETON SAND & GRAVEL INC.

3232 CARP ROAD CARP, ON CA K0A 1L0 Contact: Troy Whalen twhalen@acon.com T: (613)836-3090

F:

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:WES654STIUnique No:5629752Signed:Wes DavisReport Date:18 Aug 2023

# LIEBHERR







#### **GRAPHS**

