

# LIEBHERR

## CONSTRUCTION EQUIPMENT



### LIEBHERR LH50M 145461-1216 - Front Differential

Sample No: LH0255602

Oil Type: GEAR OIL SAE 75W90



**GENERAL RECYCLING INDUSTRIES LTD.**  
 4120 - 84 AVENUE  
 EDMONTON, AB  
 CA T6B 3H3  
 Contact: Corey MacKay  
 cmackay@trailco.ca  
 T: (587)926-1610  
 F: (780)485-4294



#### SAMPLE INFORMATION

Sample Number	LH0255602	---	---	---
Sample Date	26 Jun 2023	---	---	---
Machine Hours	1086	---	---	---
Oil Hours	0	---	---	---
Oil Changed	N/A	---	---	---
Sample Status	NORMAL	---	---	---



#### OIL CONDITION

Visc @ 40°C	cSt	98.9	---	---	---
-------------	-----	------	-----	-----	-----



#### CONTAMINATION

Silicon	ppm	2	---	---	---
Sodium	ppm	<1	---	---	---
Potassium	ppm	<1	---	---	---



#### WEAR METALS

Iron	ppm	9	---	---	---
Copper	ppm	34	---	---	---
Lead	ppm	<1	---	---	---
Tin	ppm	0	---	---	---
Aluminum	ppm	<1	---	---	---
Chromium	ppm	0	---	---	---
Molybdenum	ppm	0	---	---	---
Nickel	ppm	<1	---	---	---
Titanium	ppm	0	---	---	---
Silver	ppm	0	---	---	---
Manganese	ppm	<1	---	---	---
Vanadium	ppm	0	---	---	---



#### ADDITIVES

Calcium	ppm	13	---	---	---
Magnesium	ppm	<1	---	---	---
Zinc	ppm	23	---	---	---
Phosphorus	ppm	1307	---	---	---
Barium	ppm	2	---	---	---
Boron	ppm	308	---	---	---

#### Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 75W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

**Depot:** GEN156EDM  
**Unique No:** 5629930  
**Signed:** Wes Davis  
**Report Date:** 18 Aug 2023



### GRAPHS

