

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR LH60M 145111-1217 - Diesel Engine

Sample No: LH0261759

Oil Type: DIESEL ENGINE OIL SAE 40



SAMPLE INFORMATION

Sample Number	LH0261759	LH0266083	LH0261354	---
Sample Date	06 Sep 2023	20 Jun 2023	27 Apr 2023	---
Machine Hours	2048	1188	558	---
Oil Hours	0	0	0	---
Oil Changed	Changed	Changed	Changed	---
Sample Status	NORMAL	NORMAL	NORMAL	---

RAM IRON AND METAL

60 Ashwarren Road
TORONTO, ON
CA M3J 1Z5
Contact: PETER RACCO
PETER@RAMIRON.COM
T: (416)630-4545
F: (416)630-5258



OIL CONDITION

Visc @ 100°C	cSt	12.6	12.8	11.9	---
Oxidation (PA)	%	92	100	225	---



CONTAMINATION

Soot %	%	0	0	0	---
Nitration (PA)	%	85	84	109	---
Sulfation (PA)	%	67	65	115	---
Glycol	%	NEG	NEG	NEG	---
Fuel	%	<1.0	<1.0	1.8	---
Silicon	ppm	7	7	9	---
Sodium	ppm	2	2	2	---
Potassium	ppm	6	2	3	---

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.



WEAR METALS

Iron	ppm	7	7	15	---
Copper	ppm	9	65	237	---
Lead	ppm	1	4	10	---
Tin	ppm	<1	<1	1	---
Aluminum	ppm	2	1	3	---
Chromium	ppm	<1	<1	2	---
Molybdenum	ppm	58	57	46	---
Nickel	ppm	0	0	<1	---
Titanium	ppm	0	0	<1	---
Silver	ppm	0	0	0	---
Manganese	ppm	<1	<1	2	---
Vanadium	ppm	0	0	0	---



ADDITIVES

Calcium	ppm	1040	1091	1412	---
Magnesium	ppm	962	971	926	---
Zinc	ppm	1142	1130	826	---
Phosphorus	ppm	972	972	748	---
Barium	ppm	<1	4	31	---
Boron	ppm	2	8	93	---

Depot: RAMTOR
Unique No: 5642165
Signed: Wes Davis
Report Date: 08 Sep 2023



GRAPHS

