LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH30M 143683-1253 - Diesel Engine

Sample No: LH

Oil Type: PETRO CANADA DURON UHP 5W30

-					
SAMPLE INFORMATION					
Sample Number	LH				
Sample Date	31 Aug 2023				
Machine Hours	1000				
Oil Hours	0				
Oil Changed	Changed				
Sample Status	NORMAL				
A					

OIL CO	ONDITION			
Visc @ 100°C	cSt	11.5	 	
Oxidation (PA)	%	89	 	

CON	CONTAMINATION						
Soot %	%	0 0					
Nitration (PA)	%	85					
Sulfation (PA)	%	61					
Glycol	%	○ 0.0					
Fuel	%	<1.0					
Silicon	ppm	8					
Sodium	ppm	5					
Potassium	ppm	() <1					

(O)				
WEA	IR META	LS		
Iron	ppm	6	 	
Copper	ppm	329	 	
Lead	ppm	8	 	
Tin	ppm	○ <1	 	
Aluminum	ppm	2	 	
Chromium	ppm	○ <1	 	
Molybdenum	ppm	60	 	
Nickel	ppm	0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	○ <1	 	
Vanadium	ppm	0	 	

ADD	ITIVES			
Calcium	ppm	842	 	
Magnesium	ppm	1130	 	
Zinc	ppm	1145	 	
Phosphorus	ppm	1000	 	
Barium	ppm	3	 	
Boron	ppm	31	 	



SCIERIE MARTEL LTEE 3000 ROUTE DU LAC EST ALMA, QC CA G8B 5V2 Contact: Alain Bauchard

T: (418)668-3366 F: (418)668-2071

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:SCIALMUnique No:5642375Signed:Kevin MarsonReport Date:13 Sep 2023

LIEBHERR







GRAPHS

