## LIEBHERR

## **CONSTRUCTION EQUIPMENT**

## LIEBHERR R936LC 048600-1490 - Diesel Engine

Sample No: LH0265581

Oil Type: PETRO CANADA SUPREME 10W40 MOTOR OIL

- SAM	PLE INFO	DRMATION			
Sample Number		LH0265581	LH0186314	LH0177989	LH0162703
Sample Date		06 Sep 2023	11 Jun 2021	23 Oct 2020	31 Jan 2020
Machine Hours		2493	1641	1027	501
Oil Hours		0	0	0	0
Oil Changed		Changed	Changed	Changed	Not Changd
Sample Status		ABNORMAL	NORMAL	NORMAL	NORMAL
Visc @ 100°C	cSt	<b>12.0</b>	O 11.9	O 12.1	O 12.5
OIL	ONDITIO	JN			
Oxidation (PA)	%	69	91	164	153
<b>-</b>	70	00	0.	101	100
CON	TAMINA	TION			
	%	<b>0</b> 0	0 0	O 0	<b>0</b>
Soot %					
	%	68	80	83	78
Nitration (PA)		68 53	80 66	83 96	78 100
Nitration (PA) Sulfation (PA)	%				. 0
Nitration (PA) Sulfation (PA) Glycol	%	53	66	96	100
Nitration (PA) Sulfation (PA) Glycol Fuel	% %	53 NEG	66 NEG	96 ○ 0.0	100 NEG
Soot % Nitration (PA) Sulfation (PA) Glycol Fuel Silicon Sodium	% % % %	53 NEG ① 1	66 NEG <1.0	96 0.0 0.4	100 NEG <1.0

WEA	R METAL	.S			
Iron	ppm	<b>4</b>	<b>8</b>	<b>1</b> 7	O 11
Copper	ppm	<b>3</b>	O 63	O 271	O 212
Lead	ppm	<b>○</b> <1	<b>2</b>	<b>9</b>	<b>6</b>
Tin	ppm	<b>0</b>	O <1	O 1	0 <1
Aluminum	ppm	<b>()</b> <1	O 2	O 2	O 2
Chromium	ppm	<b>○</b> <1	O <1	O 1	O <1
Molybdenum	ppm	<b>60</b>	<b>5</b> 3	<b>50</b>	<b>46</b>
Nickel	ppm	<b>○</b> <1	O <1	<1	O <1
Titanium	ppm	0	<1	<1	<1
Silver	ppm	<b>0</b>	0	0	0
Manganese	ppm	<b>0</b>	O <1	1	<1
Vanadium	ppm	0	0	0	0

variaululli	ppiii	U	U	U	U	
ADD	DITIVES					
Calcium	ppm	<b>928</b>	O 1142	O 1452	1440	
Magnesium	ppm	1025	O 999	776	O 751	
Zinc	ppm	1213	O 1284	991	963	
Phosphorus	ppm	1088	O 990	752	785	
Barium	ppm	<b>○</b> <1	<b>6</b>	<b>37</b>	○ 33	
Boron	ppm	<b>45</b>	○ 33	<b>48</b>	O 70	



COLOURED AGGREGATES INC.
158 DON HILLOCK DRIVE,, UNIT 12-13
AURORA, ON
CA L4G 0H6
Contact: Jeff Oravecz
Jeff@colouredaggregates.com

The oil change at the time of

T: (416)491-0230

F:

#### Diagnosis

sampling has been noted. Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor. No other corrective action is recommended at this time. The fluid was specified as PETRO CANADA SUPREME 10W40 MOTOR OIL, however, a fluid match indicates that this fluid is SAE 30 Diesel Engine Oil. Please confirm the oil type and grade on your next sample.All component wear rates are normal. Light fuel dilution occurring. No other contaminants were detected in the oil. Viscosity of sample indicates oil is within SAE 30 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The condition of the oil is acceptable for the time in service.

Depot:COL158AURUnique No:5643476Signed:Kevin MarsonReport Date:15 Sep 2023


# LIEBHERR

CONSTRUCTION EQUIPMENT





#### **GRAPHS**



Report Id: COL158AUR [WCAMIS] 02582411 (Generated: 09/15/2023 11:55:20) Rev: 1

Submitted By: ?