

# LIEBHERR

## CONSTRUCTION EQUIPMENT



### LIEBHERR L556 066122-1826 - Rear Differential

Sample No: LH0271430

Oil Type: GEAR OIL SAE 80W90



#### SAMPLE INFORMATION

Sample Number	LH0271430	LH	---	---
Sample Date	02 Aug 2023	27 Mar 2023	---	---
Machine Hours	2043	1035	---	---
Oil Hours	0	0	---	---
Oil Changed	N/A	N/A	---	---
Sample Status	NORMAL	NORMAL	---	---

REVALORISATION TPOL INC.  
215 RUE DAMASE BRETON  
ST.LAMBERT DE LAUZON, QC  
CA G0S 2W0  
Contact: Service Manager



#### OIL CONDITION

Visc @ 40°C	cSt	● 191	● 194	---	---
-------------	-----	-------	-------	-----	-----

T:  
F:



#### CONTAMINATION

Silicon	ppm	● 11	● 31	---	---
Sodium	ppm	● 2	● 10	---	---
Potassium	ppm	● 0	● <1	---	---

#### Diagnosis

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Les taux d'usure de tous les composants sont normaux. Il n'y a aucun indice de contamination dans l'huile. L'état de l'huile est acceptable pour la durée de service.



#### WEAR METALS

Iron	ppm	● 68	● 393	---	---
Copper	ppm	● 34	174	---	---
Lead	ppm	● <1	● 4	---	---
Tin	ppm	● 1	● 9	---	---
Aluminum	ppm	● <1	● 2	---	---
Chromium	ppm	● <1	● 4	---	---
Molybdenum	ppm	● 0	● 0	---	---
Nickel	ppm	● 1	5	---	---
Titanium	ppm	0	<1	---	---
Silver	ppm	<1	0	---	---
Manganese	ppm	● 5	39	---	---
Vanadium	ppm	0	0	---	---



#### ADDITIVES

Calcium	ppm	● 3	● 7	---	---
Magnesium	ppm	● <1	● 3	---	---
Zinc	ppm	● 18	● 35	---	---
Phosphorus	ppm	● 2374	● 2429	---	---
Barium	ppm	● 0	● 0	---	---
Boron	ppm	● <1	● 3	---	---

Depot: REVSTL  
Unique No: 5643670  
Signed: Wes Davis  
Report Date: 14 Sep 2023



### GRAPHS

