

# LIEBHERR

## CONSTRUCTION EQUIPMENT



### LIEBHERR LH30M 143328-1253 - Diesel Engine

Sample No: LH0247999

Oil Type: DIESEL ENGINE OIL SAE 5W40



**Scierie Girard Inc.**  
5872 Rte. Bouleaux (Route 172)  
Shipshaw, QC  
CA G7P 1E3  
Contact: Service  
benoit@scieriegirard.com  
T:  
F:



#### SAMPLE INFORMATION

Sample Number	LH0247999	LH0247978	LH0247963	LH0247966
Sample Date	16 Aug 2023	03 Apr 2023	02 Mar 2023	22 Feb 2023
Machine Hours	3566	1919	500	1406
Oil Hours	0	0	0	0
Oil Changed	Not Changd	Changed	N/A	N/A
Sample Status	NORMAL	NORMAL	ABNORMAL	NORMAL



#### OIL CONDITION

Visc @ 100°C	cSt	12.9	12.6	12.0	11.6
Oxidation (PA)	%	82	83	209	111



#### CONTAMINATION

Soot %	%	0	0	0	0
Nitration (PA)	%	83	83	98	86
Sulfation (PA)	%	58	65	116	73
Glycol	%	NEG	NEG	NEG	NEG
Fuel	%	<1.0	<1.0	0.5	0.8
Silicon	ppm	3	3	9	8
Sodium	ppm	5	5	2	5
Potassium	ppm	2	<1	2	<1



#### WEAR METALS

Iron	ppm	3	5	10	7
Copper	ppm	3	13	334	132
Lead	ppm	<1	<1	10	4
Tin	ppm	<1	<1	1	<1
Aluminum	ppm	<1	1	4	2
Chromium	ppm	0	<1	1	<1
Molybdenum	ppm	57	57	46	56
Nickel	ppm	0	<1	0	0
Titanium	ppm	0	<1	<1	<1
Silver	ppm	<1	0	0	0
Manganese	ppm	0	<1	1	<1
Vanadium	ppm	0	0	0	0



#### ADDITIVES

Calcium	ppm	816	877	1510	965
Magnesium	ppm	1107	1145	929	1108
Zinc	ppm	1195	1221	885	1174
Phosphorus	ppm	975	1096	809	1008
Barium	ppm	<1	<1	32	5
Boron	ppm	18	32	105	34

#### Diagnosis

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Les taux d'usure de tous les composants sont normaux. Il n'y a aucun indice de contamination dans l'huile. L'état de l'huile est acceptable pour la durée de service.

Depot: SCISHI  
Unique No: 5645937  
Signed: Wes Davis  
Report Date: 25 Sep 2023



### GRAPHS

