LIEBHERR

CONSTRUCTION EQUIPMENT



Sample No: LH0265557

Oil Type: PETRO CANADA TRAXON 75W90 SYNTHETIC

a							
SAMI	PLE INFO	RMATION					
Sample Number		LH0265557	LH0186308				
Sample Date		20 Sep 2023	24 Sep 2021				
Machine Hours		4142	2934				
Oil Hours		0	0				
Oil Changed		Changed	Changed				
Sample Status		NORMAL	NORMAL				
OIL CONDITION							
Visc @ 40°C	cSt	186	170				
CONTAMINATION							
Silicon	ppm	9	10				
Sodium	ppm	4	4				
Potaccium	nnm	2	03				

Potassium	ppm	2	3	
WEA	R METALS			
Iron	ppm	110	O 121	
Copper	ppm	0 <1	O <1	
Lead	ppm	() <1	O <1	
Tin	ppm	0	0	
Aluminum	ppm	2	O 1	
Chromium	ppm	1	O 2	
Molybdenum	ppm	0	O 0	
Nickel	ppm	() <1	<1	
Titanium	ppm	0	0	
Silver	ppm	<1	0	
Manganese	ppm	() <1	O 2	
Vanadium	ppm	0	0	
100				

ADDITIVES							
Calcium	ppm	14	25				
Magnesium	ppm	2	O 4				
Zinc	ppm	19	26				
Phosphorus	ppm	2124	O 1375				
Barium	ppm	65	219				
Boron	ppm	13	12				

Report Id: AMEHAM [WCAMIS] 02587302 (Generated: 10/06/2023 11:42:03) Rev: 1



American Iron and Metal

75 Steel City Court Hamilton, ON CA L8H 3Y2

Contact: Heavy Equipment

hamiltonmobileassetmaintenance@aim-recycling.com

T: (905)547-5533 F: (905)544-5671

Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill.

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

Depot: AMEHAM
Unique No: 5656368
Signed: Wes Davis
Report Date: 06 Oct 2023





GRAPHS

