LIEBHERR

CONSTRUCTION EQUIPMENT

[(340369)] LIEBHERR R920 045718-1705 - Left Final Drive

Sample No: LH0274847

Oil Type: LIEBHERR GEAR BASIC 90 LS

SAN	APLE INFO	DRMATION		
Sample Number		LH0274847	LH0195626	
Sample Date		06 Oct 2023	12 Jul 2022	
Machine Hours		4924	2793	
Oil Hours		0	0	
Oil Changed		Changed	Not Changd	
Sample Status		NORMAL	NORMAL	
<u> </u>				
OIL	CONDITION	ON		
/isc @ 40°C	cSt	90.8	O 91.7	
-1	001	00.0	0 0 1.7	
CON	TAMINA	TION		
	IAMINA	IION		
Silicon	ppm	54	O 18	
Sodium	ppm	4	0 2	
Potassium	ppm	5	0 2	
◎ WE	AR META	LS		
lron	ppm	176	6 7	
Copper	ppm	() <1	0	
_ead	ppm	0	0	
Γin	ppm	0	0	
Aluminum	ppm	14	4	
Chromium	ppm	2	O <1	
Molybdenum	ppm	0	0	
Nickel	ppm	○ <1	0	
Titanium	ppm	0	<1	
Silver	ppm	<1	0	
Manganese	ppm	1	O <1	
/anadium	ppm	0	0	
ADD	ITIVES			
Calcium	ppm	15	O 15	
Magnesium	ppm	5	0 6	

0 1274

 \bigcirc <1

288



CLOUTHIER VENTURES LTD.

59 MATTHEWS STREET, R.R. # 5 PEMBROKE, ON

CA K8A 0A6

Contact: Travis Bennett tbennett@clouthierconst.com

T: (613)735-6531 F: (613)735-2769

Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill.

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

Depot:CLOPEMUnique No:5657774Signed:Wes DavisReport Date:12 Oct 2023

1292

302

1

Phosphorus

Barium

Boron

ppm

ppm

ppm

LIEBHERR







GRAPHS

