LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR L566 071885-1758 - Splitter Box

0<1

Sample No: LH0276160

Potassium

Oil Type: GEAR OIL SAE 75W90

ppm

_							
U SAN	APLE INFO	DRMATION					
Sample Number		LH0276160	LH0261534				
Sample Date		12 Oct 2023	11 Jun 2023				
Machine Hours		937	500				
Oil Hours		0	0				
Oil Changed		N/A	Changed				
Sample Status		NORMAL	NORMAL				
OIL CONDITION							
Visc @ 40°C	cSt	102	189				
and the second							
CONTAMINATION							
Silicon	ppm	2	O 2				
Sodium	ppm	2	O 7				

WEAR METALS							
PQ			O 0				
Iron	ppm	55	O 205				
Copper	ppm	() <1	0 2				
Lead	ppm	○ <1	O <1				
Tin	ppm	0	0				
Aluminum	ppm	○ <1	3				
Chromium	ppm	() <1	O <1				
Molybdenum	ppm	2	4				
Nickel	ppm	3	0 8				
Titanium	ppm	0	<1				
Silver	ppm	<1	0				
Manganese	ppm	○ <1	5				
Vanadium	ppm	0	0				
100							

variadium	ppiii	U	U					
ADDITIVES								
Calcium	ppm	18	19					
Magnesium	ppm	4	13					
Zinc	ppm	32	95					
Phosphorus	ppm	1378	2413					
Barium	ppm	3	15					
Boron	ppm	266	5					





MONAGHAN MUSHROOMS LTD

7345 GUELPH LINE CAMPBELLVILLE, ON CA LOP 1B0

Contact: Steven Cargill

s.cargill@monaghan-mushrooms.com

T: F:

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 75W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: MONCAM
Unique No: 5658094
Signed: Wes Davis
Report Date: 13 Oct 2023

LIEBHERR

CONSTRUCTION EQUIPMENT





GRAPHS

