

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR LH60M 141511-1217 - Front Differential

Sample No: LH0246252

Oil Type: GEAR OIL SAE 75W90



Radius Recycling Canada Ltd.
 12195 Musqueam Dr.
 Surrey, BC
 CA V3V 3T2
 Contact: Chris Trinkunas
 ctrinkunas@rds.com
 T:
 F: (604)580-1922



SAMPLE INFORMATION

Sample Number	LH0246252	---	---	---
Sample Date	08 Sep 2023	---	---	---
Machine Hours	1531	---	---	---
Oil Hours	0	---	---	---
Oil Changed	Not Chngd	---	---	---
Sample Status	NORMAL	---	---	---



OIL CONDITION

Visc @ 40°C	cSt	● 121	---	---	---
-------------	-----	-------	-----	-----	-----



CONTAMINATION

Silicon	ppm	● 5	---	---	---
Sodium	ppm	● 1	---	---	---
Potassium	ppm	● 0	---	---	---



WEAR METALS

Iron	ppm	● 8	---	---	---
Copper	ppm	● 15	---	---	---
Lead	ppm	● <1	---	---	---
Tin	ppm	● 0	---	---	---
Aluminum	ppm	● 0	---	---	---
Chromium	ppm	● 0	---	---	---
Molybdenum	ppm	● 0	---	---	---
Nickel	ppm	● <1	---	---	---
Titanium	ppm	0	---	---	---
Silver	ppm	<1	---	---	---
Manganese	ppm	● 0	---	---	---
Vanadium	ppm	0	---	---	---



ADDITIVES

Calcium	ppm	● 20	---	---	---
Magnesium	ppm	● <1	---	---	---
Zinc	ppm	● 14	---	---	---
Phosphorus	ppm	● 1209	---	---	---
Barium	ppm	● 96	---	---	---
Boron	ppm	● 221	---	---	---

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 75W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: AMISUR
 Unique No: 5658832
 Signed: Wes Davis
 Report Date: 17 Oct 2023



GRAPHS

