

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR A904 056759-005 - Front Differential

Sample No: LH

Oil Type: GEAR OIL SAE 75W90



LIEBHERR CANADA LTEE
 444 AVENUE DE LA FRICHE
 DOLBEAU-MISTASSINI, QC
 CA G8L 3M7
 Contact: Luc Trottier
 luc.trottier@liebherr.com
 T:
 F: (418)276-9844



SAMPLE INFORMATION

Sample Number	LH	---	---	---
Sample Date	18 Oct 2023	---	---	---
Machine Hours	14788	---	---	---
Oil Hours	0	---	---	---
Oil Changed	N/A	---	---	---
Sample Status	NORMAL	---	---	---



OIL CONDITION

Visc @ 40°C	cSt	● 98.9	---	---	---
-------------	-----	--------	-----	-----	-----



CONTAMINATION

Silicon	ppm	● <1	---	---	---
Sodium	ppm	● 2	---	---	---
Potassium	ppm	● 0	---	---	---



WEAR METALS

Iron	ppm	● 10	---	---	---
Copper	ppm	● <1	---	---	---
Lead	ppm	● <1	---	---	---
Tin	ppm	● 0	---	---	---
Aluminum	ppm	● 0	---	---	---
Chromium	ppm	● 0	---	---	---
Molybdenum	ppm	● 0	---	---	---
Nickel	ppm	● <1	---	---	---
Titanium	ppm	● 0	---	---	---
Silver	ppm	● <1	---	---	---
Manganese	ppm	● 0	---	---	---
Vanadium	ppm	● 0	---	---	---



ADDITIVES

Calcium	ppm	● 2	---	---	---
Magnesium	ppm	● 0	---	---	---
Zinc	ppm	● 2	---	---	---
Phosphorus	ppm	● 1407	---	---	---
Barium	ppm	● <1	---	---	---
Boron	ppm	● 256	---	---	---

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 75W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: LBADOL
 Unique No: 5668903
 Signed: Wes Davis
 Report Date: 25 Oct 2023



GRAPHS

