## LIEBHERR

### **CONSTRUCTION EQUIPMENT**

### LIEBHERR R924 054969-1487 - Left Final Drive

Sample No: LH0277740

Oil Type: LIEBHERR GEAR BASIC 90 LS

SAN	APLE INFO	DRMATION		
Sample Number		LH0277740	 	
Sample Date		17 Oct 2023	 	
Machine Hours		2060	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
A Carriero		HOIMAL		
OIL	CONDITIO	DN		
Visc @ 40°C	cSt	98.4	 	
E CON	ITAMINA	TION		
Silicon	ppm	<b>6</b>	 	
Sodium	ppm	<b>2</b>	 	
Potassium	ppm	<b>O</b> <1	 	
	AR META			
Iron	ppm	<b>52</b>	 	
Copper	ppm	<b>○</b> <1	 	
Lead	ppm	○ <1	 	
Tin	ppm	<b>0</b>	 	
Aluminum	ppm	<b>2</b>	 	
Chromium	ppm	<b>2</b>	 	
Molybdenum	ppm	<b>0</b>	 	
Nickel	ppm	<b>○</b> <1	 	
Titanium	ppm	<b>0</b>	 	
Silver	ppm	<1	 	
Manganese	ppm	<b>0</b>	 	
Vanadium	ppm	0	 	
ADD	ITIVES			
Calcium	ppm	<b>8</b>	 	
Magnesium	ppm	O 2	 	
<b>U</b>	T- F-			



#### **CLOUTHIER VENTURES LTD.**

59 MATTHEWS STREET, R.R. # 5 PEMBROKE, ON

CA K8A 0A6

Contact: Travis Bennett tbennett@clouthierconst.com

T: (613)735-6531 F: (613)735-2769

#### Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill.

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

Depot:CLOPEMUnique No:5672195Signed:Wes DavisReport Date:09 Nov 2023

17

**1** 

1245

294

ppm

ppm

ppm

ppm

Zinc

Barium

Boron

Phosphorus

# LIEBHERR

CONSTRUCTION EQUIPMENT





#### **GRAPHS**

