LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH40C 146602-1527 - Diesel Engine

Sample No: LH0266327

Oil Type: PETRO CANADA SUPREME 5W30

5					
SAM	PLE INFOR	MATION			
Sample Number		LH0266327	LH0266326		
Sample Date		01 Nov 2023	10 Aug 2023		
Machine Hours		1016	530		
Oil Hours		0	0		
Oil Changed		Changed	Changed		
Sample Status		NORMAL	NORMAL		
OIL CONDITION					
Visc @ 100°C	cSt	13.3	12.0		
Oxidation (PA)	%	78	208		

CONTAMINATION					
Soot %	%	0 0	O 0		
Nitration (PA)	%	64	99		
Sulfation (PA)	%	59	114		
Glycol	%	NEG	NEG		
Fuel	%	<1.0	O 1.6		
Silicon	ppm	6	O 10		
Sodium	ppm	2	3		
Potassium	ppm	0	O 4		

WEAL	R METALS			
		0 -	0.10	
Iron	ppm	5	1 3	
Copper	ppm	95	206	
Lead	ppm	3	8	
Tin	ppm	0 <1	1	
Aluminum	ppm	2	4	
Chromium	ppm	0 <1	O 2	
Molybdenum	ppm	57	45	
Nickel	ppm	0	O 0	
Titanium	ppm	0	<1	
Silver	ppm	0 <1	O 0	
Manganese	ppm	0	1	
Vanadium	ppm	0	0	

ADDITIVES					
Calcium	ppm	1064	O 1349		
Magnesium	ppm	922	958		
Zinc	ppm	1126	○ 859		
Phosphorus	ppm	907	O 762		
Barium	ppm	2	O 17		
Boron	ppm	14	O 104		





CALGARY METALS (1985) LTD.

3415 OGDEN RD. SE. CALGARY, AB CA T2G 4N4

Contact: Steve Goodzeck sgoodzeck@calgarymetal.com

T: (403)262-4542

F:

Diagnosis

Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. Viscosity of sample indicates oil is within SAE 40 range, advise investigate. The condition of the oil is acceptable for the time in service.

Depot:CAL341CALUnique No:5672379Signed:Bill QuesnelReport Date:10 Nov 2023

LIEBHERR

CONSTRUCTION EQUIPMENT





GRAPHS

