LIEBHERR

Oil Hours



 Oil Changed
 Changed
 -- -- --

 Sample Status
 NORMAL
 -- -- --

 OIL CONDITION

 Visc @ 100°C
 cSt
 ① 11.7
 -- -- --

 Oxidation (PA)
 %
 83
 -- -- --

1									
CONTAMINATION									
Water	%	NEG							
Soot %	%	0							
Nitration (PA)	%	85							
Sulfation (PA)	%	60							
Glycol	%	0.0							
Fuel	%	<1.0							
Silicon	ppm	7							
Sodium	ppm	4							
Potassium	ppm	9							

WEA	R META	LS		
Iron	ppm	6	 	
Copper	ppm	9	 	
Lead	ppm	1	 	
Tin	ppm	0	 	
Aluminum	ppm	1	 	
Chromium	ppm	0	 	
Molybdenum	ppm	48	 	
Nickel	ppm	○ <1	 	
Titanium	ppm	0	 	
Silver	ppm	○ <1	 	
Manganese	ppm	0	 	
Vanadium	ppm	0	 	

VES				
opm C) 1041			
opm	941			
opm	1213			
opm	1014			
opm) <1			
opm	39			
	ppm Copm Copm Copm Copm Copm Copm Copm C	ppm 941 ppm 1213 ppm 01014 ppm < 1	ppm	ppm

10 760A HENRI BOURASSA EST MONTREAL, QC CA H1C 1S9 Contact: M. Couturier mcouturier@delsan-aim.com

T: (514)703-7024

F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: AIMMON
Unique No: 5694597
Signed: Wes Davis
Report Date: 08 Dec 2023

LIEBHERR

CONSTRUCTION EQUIPMENT





GRAPHS

