

# LIEBHERR

## CONSTRUCTION EQUIPMENT



### 144379-1218 - Rear Differential

Sample No: LH0255209

Oil Type: GEAR OIL SAE 80W90



#### SAMPLE INFORMATION

Sample Number	LH0255209	LH0255198	---	---
Sample Date	06 Dec 2023	09 Jun 2023	---	---
Machine Hours	2248	1110	---	---
Oil Hours	0	0	---	---
Oil Changed	N/A	N/A	---	---
Sample Status	NORMAL	NORMAL	---	---

#### American Iron and Metal

10305 Metropolitaine Est, Garage porte 13  
Montreal, QC

CA H1B 1A1

Contact: Sebastien Liautaud

sliataud@aimrecyclinggroup.com

T:

F:



#### OIL CONDITION

Visc @ 40°C	cSt	● 162	● 161	---	---
-------------	-----	-------	-------	-----	-----



#### CONTAMINATION

Water	%	NEG	NEG	---	---
Silicon	ppm	● 10	● 8	---	---
Sodium	ppm	● 4	● 4	---	---
Potassium	ppm	● 0	● <1	---	---

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.



#### WEAR METALS

Iron	ppm	● 14	● 8	---	---
Copper	ppm	● 6	● 4	---	---
Lead	ppm	● <1	● 0	---	---
Tin	ppm	● 0	● 0	---	---
Aluminum	ppm	● <1	● <1	---	---
Chromium	ppm	● 0	● 0	---	---
Molybdenum	ppm	● 0	● 0	---	---
Nickel	ppm	● <1	● 0	---	---
Titanium	ppm	0	0	---	---
Silver	ppm	<1	0	---	---
Manganese	ppm	● 0	● <1	---	---
Vanadium	ppm	0	0	---	---



#### ADDITIVES

Calcium	ppm	● 19	● 7	---	---
Magnesium	ppm	● <1	● <1	---	---
Zinc	ppm	● 11	● 8	---	---
Phosphorus	ppm	● 1424	● 1464	---	---
Barium	ppm	● 175	● 192	---	---
Boron	ppm	● 60	● 63	---	---

Depot: LACMON

Unique No: 5695761

Signed: Wes Davis

Report Date: 12 Dec 2023



### GRAPHS

