# LIEBHERR

**CONSTRUCTION EQUIPMENT** 

### LIEBHERR LH30M 153712-1253 - Rear Right Wheel Hub

Sample No: LH

Oil Type: LIEBHERR GEAR BASIC 90 LS

| <b>5</b>          |  |             |  |  |  |  |
|-------------------|--|-------------|--|--|--|--|
| SAMPLEINFORMATION |  |             |  |  |  |  |
| Sample Number     |  | LH          |  |  |  |  |
| Sample Date       |  | 14 Dec 2023 |  |  |  |  |
| Machine Hours     |  | 500         |  |  |  |  |
| Oil Hours         |  | 0           |  |  |  |  |
| Oil Changed       |  | Changed     |  |  |  |  |
| Sample Status     |  | ABNORMAL    |  |  |  |  |
| <b>A</b>          |  |             |  |  |  |  |



| CONTAMINATION |     |              |  |  |  |  |  |
|---------------|-----|--------------|--|--|--|--|--|
| Water         | %   | NEG          |  |  |  |  |  |
| Silicon       | ppm | <b>6</b>     |  |  |  |  |  |
| Sodium        | ppm | <b>15</b>    |  |  |  |  |  |
| Potassium     | ppm | <b>()</b> <1 |  |  |  |  |  |

| (O) WE     |         |             |      |  |
|------------|---------|-------------|------|--|
| ₩ WE       | AR META | LS          |      |  |
| Iron       | ppm     | <b>14</b>   | <br> |  |
| Copper     | ppm     | <b>3</b>    | <br> |  |
| Lead       | ppm     | <b>○</b> <1 | <br> |  |
| Tin        | ppm     | 0           | <br> |  |
| Aluminum   | ppm     | <b>1</b>    | <br> |  |
| Chromium   | ppm     | <b>○</b> <1 | <br> |  |
| Molybdenum | ppm     | <b>0</b>    | <br> |  |
| Nickel     | ppm     | <b>O</b> <1 | <br> |  |
| Titanium   | ppm     | 0           | <br> |  |
| Silver     | ppm     | <1          | <br> |  |
| Manganese  | ppm     | <b>1</b>    | <br> |  |
| Vanadium   | ppm     | 0           | <br> |  |
|            |         |             |      |  |

| ADDITIVES |                                 |  |  |  |  |  |
|-----------|---------------------------------|--|--|--|--|--|
| ppm       | 3696                            |  |  |  |  |  |
| ppm       | <b>11</b>                       |  |  |  |  |  |
| ppm       | 1457                            |  |  |  |  |  |
| ppm       | 1145                            |  |  |  |  |  |
| ppm       | <b>()</b> <1                    |  |  |  |  |  |
| ppm       | 110                             |  |  |  |  |  |
|           | ppm<br>ppm<br>ppm<br>ppm<br>ppm | ppm 3696 ppm 11 ppm 1457 ppm 1145 ppm 0 <1 | ppm       3696          ppm       11          ppm       1457          ppm       1145          ppm       ○ <1 | ppm     3696       ppm     ○ 11       ppm     1457       ppm     1145       ppm     ○ <1 |  |  |



#### Innovation Industrielle Boivin Inc.

2205 de la Fonderie Chicoutimi, QC CA G7H 8B9

Contact: Service Manager

T: F:

#### Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill.

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Viscosity of sample indicates oil is within SAE 80 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The condition of the oil is acceptable for the time in service.

Depot: INN220CHI
Unique No: 5696996
Signed: Kevin Marson
Report Date: 19 Dec 2023

## LIEBHERR

CONSTRUCTION EQUIPMENT





#### **GRAPHS**

