LIEBHERR

CONSTRUCTION EQUIPMENT



Sample No: LH0257207

Oil Type: PETRO CANADA DURATRAN

5						
SAMPLEINFORMATION						
Sample Number	LH0257207	LH0257174				
Sample Date	15 Dec 2023	18 May 2023				
Machine Hours	4000	978				
Oil Hours	0	0				
Oil Changed	Changed	N/A				
Sample Status	NORMAL	NORMAL				

OILCO	NDITION			
Visc @ 40°C	cSt	36.3	42.7	
Visc @ 40°C	cSt	36.3	42.7	

CONTAMINATION								
Water	%	NEG	NEG					
Silicon	ppm	8	08					
Sodium	ppm	2	17					
Potassium	ppm	0	O 7					

10				
₩ WEA	R METAL	S		
Iron	ppm	0 7	0 8	
Copper	ppm	1	O 2	
Lead	ppm	 <1	O <1	
Tin	ppm	0	O 0	
Aluminum	ppm	2	O 1	
Chromium	ppm	0	O 0	
Molybdenum	ppm	0	0	
Nickel	ppm	0	O 0	
Titanium	ppm	0	<1	
Silver	ppm	0	O 2	
Manganese	ppm	0	O <1	
Vanadium	ppm	0	0	

ADDITIVES							
Calcium	ppm	3530	○ 3653				
Magnesium	ppm	8	O 7				
Zinc	ppm	1355	O 1429				
Phosphorus	ppm	1140	O 1260				
Barium	ppm	0	0				
Boron	ppm	99	100				



PRODUITS FORESTIERS D.G. LTEE 313 RANG ST-JOSEPH STE-AURELIE, QC CA G0M 1M0 Contact: Roger.

T: (418)593-3547 F: (418)593-3633

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the fluid.

Viscosity of sample indicates oil is within SAE 70W80 range, advise investigate. The condition of the fluid is acceptable for the time in service.

Depot:PRO9STEUnique No:5707082Signed:Kevin MarsonReport Date:03 Jan 2024

LIEBHERR

CONSTRUCTION EQUIPMENT





GRAPHS

