# LIEBHERR

**CONSTRUCTION EQUIPMENT** 

### LIEBHERR A904 056759-005 - 1 Final Drive

Sample No: LH

Oil Type: GEAR OIL SAE 80W90

SAN	APLE INFO	DRMATION		
Sample Number		LH	 	
Sample Date		04 Jan 2024	 	
Machine Hours		1176	 	
Oil Hours		0	 	
Oil Changed		N/A	 	
Sample Status		NORMAL	 	
OIL	CONDITIO	ON		
OIL OVISC @ 40°C	<b>CONDITIO</b>	ON () 130	 	
Visc @ 40°C		<b>130</b>	 	
Visc @ 40°C	cSt	<b>130</b>		
Visc @ 40°C	cSt	(a) 130		
Visc @ 40°C  CON  Water	cSt	130 ATION NEG	 	

WEA	R METALS			
Iron	ppm	<b>58</b>	 	
Copper	ppm	<b>0</b> <1	 	
Lead	ppm	<b>0</b>	 	
Tin	ppm	<b>0</b>	 	
Aluminum	ppm	<b>○</b> <1	 	
Chromium	ppm	<b>○</b> <1	 	
Molybdenum	ppm	<b>0</b>	 	
Nickel	ppm	<b>○</b> <1	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	<b>○</b> <1	 	
Vanadium	ppm	0	 	

variaulum	ppiii	U						
ADDITIVES								
Calcium	ppm	<b>34</b>						
Magnesium	ppm	<b></b> <1						
Zinc	ppm	<b>37</b>						
Phosphorus	ppm	<b>1141</b>						
Barium	ppm	<b>1</b>						
Boron	ppm	<b>O</b> <1						





LIEBHERR CANADA LTEE
444 AVENUE DE LA FRICHE
DOLBEAU-MISTASSINI, QC
CA G8L 3M7
Contact: Martin Gagnon
martin.gagnon@liebherr.com

F: (418)276-9844

#### Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: LBADOL
Unique No: 5707915
Signed: Wes Davis
Report Date: 05 Jan 2024

# LIEBHERR







### **GRAPHS**

