
LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH40M 146308-1215 - Transmission (Manual)

Sample No: LH0281090

Oil Type: PETRO CANADA 10W40



Sample S	otatus		NORMAL	 	
	OIL CO	NDITION			
Visc @ 40	0°C	cSt	55.0	 	

CONT	CONTAMINATION							
Water	%	NEG						
Silicon	ppm	2						
Sodium	ppm	34						
Potassium	ppm	4	***					

○ 10○ 21			
() <1			
O <1			
3			
0			
0			
○ <1			
0			
0			
10			
0			
	○ <1 ○ 3 ○ 0 ○ 0 ○ <1 ○ 0 ○ 0 ○ 10	○ <1 ○ 3 ○ 0 ○ 0 ○ 0 ○ 0 ○ 10	○ <1

ADDITIVES						
Calcium	ppm	3106				
Magnesium	ppm	8				
Zinc	ppm	1093				
Phosphorus	ppm	997				
Barium	ppm	<1				
Boron	ppm	4				



RICHMOND STEEL RECYCLING

955 ORD ROAD KAMLOOPS, BC CA V2B 7B5

Contact: Service Manager

T: F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the fluid. The fluid viscosity is lower than typical, possibly indicating the addition of lighter grade fluid. The condition of the fluid is acceptable for the time in service.

Depot: RIC955KAM
Unique No: 5708260
Signed: Kevin Marson
Report Date: 10 Jan 2024

LIEBHERR







GRAPHS

