

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR L556 054860-1332 - Rear Differential

Sample No: LH

Oil Type: LIEBHERR GEAR BASIC 90 LS



SAMPLE INFORMATION

Sample Number	LH	LH	LH	LH0153027
Sample Date	12 Jan 2024	08 Dec 2023	18 Jul 2023	14 Apr 2023
Machine Hours	15500	15000	13966	13063
Oil Hours	0	0	0	0
Oil Changed	Changed	Changed	Changed	Changed
Sample Status	NORMAL	NORMAL	NORMAL	NORMAL

GROUPE LIGNAREX INC.
 7700 CHEMIN DE LA BATTURE
 LA BAIE, QC
 CA G7B 3P6
 Contact: Service Manager



OIL CONDITION

Visc @ 40°C	cSt	180	178	185	194

T:
F:



CONTAMINATION

Water	%	NEG	NEG	NEG	NEG
Silicon	ppm	<1	1	1	2
Sodium	ppm	<1	2	1	2
Potassium	ppm	0	0	<1	<1

Diagnosis

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Les taux d'usure de tous les composants sont normaux. Il n'y a aucun indice de contamination dans l'huile. L'état de l'huile est acceptable pour la durée de service.



WEAR METALS

Iron	ppm	20	41	20	31
Copper	ppm	4	8	5	10
Lead	ppm	0	<1	0	0
Tin	ppm	0	0	0	<1
Aluminum	ppm	<1	<1	<1	0
Chromium	ppm	0	0	0	0
Molybdenum	ppm	<1	2	2	3
Nickel	ppm	0	<1	0	0
Titanium	ppm	0	0	0	0
Silver	ppm	0	<1	0	0
Manganese	ppm	0	<1	<1	<1
Vanadium	ppm	0	0	0	0



ADDITIVES

Calcium	ppm	3	6	5	<1
Magnesium	ppm	0	0	<1	<1
Zinc	ppm	6	9	7	7
Phosphorus	ppm	2323	2231	2408	2364
Barium	ppm	0	<1	0	0
Boron	ppm	<1	2	2	<1

Depot: GROLAB
 Unique No: 5710560
 Signed: Wes Davis
 Report Date: 17 Jan 2024



GRAPHS

