

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR LH50M 124712-1216 - Rear Right Wheel Hub

Sample No: LH0277313

Oil Type: GEAR OIL SAE 80W90



SCIERIE DION & FILS INC
 147 RUE ST-ALEXIS
 ST.RAYMOND, QC
 CA G3L 1S1
 Contact: Marc Lamarre
 mlamarre@scieriedion.com
 T: (418)337-2265
 F: (418)337-4142



SAMPLE INFORMATION

Sample Number	LH0277313	LH0265520	LH0243027	LH0180729
Sample Date	16 Jan 2024	07 Jun 2023	09 Dec 2022	05 May 2022
Machine Hours	12176	10063	8175	5940
Oil Hours	0	0	0	0
Oil Changed	Changed	Changed	N/A	Changed
Sample Status	NORMAL	NORMAL	NORMAL	NORMAL



OIL CONDITION

Visc @ 40°C	cSt	194	186	183	172
-------------	-----	-----	-----	-----	-----



CONTAMINATION

Water	%	NEG	NEG	NEG	NEG
Silicon	ppm	3	1	3	2
Sodium	ppm	1	2	2	2
Potassium	ppm	1	<1	0	<1



WEAR METALS

Iron	ppm	28	19	48	37
Copper	ppm	1	2	5	2
Lead	ppm	0	0	<1	0
Tin	ppm	0	0	0	0
Aluminum	ppm	<1	<1	<1	<1
Chromium	ppm	0	0	0	0
Molybdenum	ppm	0	0	0	0
Nickel	ppm	<1	<1	<1	<1
Titanium	ppm	0	0	0	0
Silver	ppm	0	0	<1	0
Manganese	ppm	0	<1	<1	<1
Vanadium	ppm	0	0	0	0



ADDITIVES

Calcium	ppm	6	<1	7	11
Magnesium	ppm	<1	<1	2	0
Zinc	ppm	5	3	11	5
Phosphorus	ppm	2224	2444	2397	2427
Barium	ppm	0	0	0	0
Boron	ppm	<1	<1	1	2

Diagnosis

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Les taux d'usure de tous les composants sont normaux. Il n'y a aucun indice de contamination dans l'huile. L'état de l'huile est acceptable pour la durée de service.

Depot: SCISTR
 Unique No: 5710832
 Signed: Wes Davis
 Report Date: 18 Jan 2024



GRAPHS

