

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR LH50M 152152-1216 - Swing Drive

Sample No: LH0265533

Oil Type: GEAR OIL SAE 80W90



SCIERIE DION & FILS INC
 147 RUE ST-ALEXIS
 ST.RAYMOND, QC
 CA G3L 1S1
 Contact: Marc Lamarre
 mlamarre@scieriedion.com
 T: (418)337-2265
 F: (418)337-4142



SAMPLE INFORMATION

Sample Number	LH0265533	LH0248362	LH0271499	---
Sample Date	17 Jan 2024	04 Oct 2023	11 Sep 2023	---
Machine Hours	2579	1021	630	---
Oil Hours	0	0	0	---
Oil Changed	Changed	Changed	Changed	---
Sample Status	NORMAL	NORMAL	NORMAL	---



OIL CONDITION

Visc @ 40°C	cSt	180	193	185	---
-------------	-----	-----	-----	-----	-----



CONTAMINATION

Water	%	NEG	NEG	NEG	---
Silicon	ppm	2	2	10	---
Sodium	ppm	<1	1	4	---
Potassium	ppm	<1	<1	<1	---



WEAR METALS

Iron	ppm	61	55	263	---
Copper	ppm	71	61	178	---
Lead	ppm	2	2	5	---
Tin	ppm	4	4	20	---
Aluminum	ppm	<1	<1	2	---
Chromium	ppm	0	0	2	---
Molybdenum	ppm	0	0	0	---
Nickel	ppm	<1	<1	<1	---
Titanium	ppm	0	0	0	---
Silver	ppm	0	<1	0	---
Manganese	ppm	0	0	3	---
Vanadium	ppm	0	0	0	---



ADDITIVES

Calcium	ppm	10	11	25	---
Magnesium	ppm	5	2	<1	---
Zinc	ppm	17	13	37	---
Phosphorus	ppm	2310	2228	2407	---
Barium	ppm	<1	2	14	---
Boron	ppm	2	2	10	---

Diagnosis

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Les taux d'usure de tous les composants sont normaux. Il n'y a aucun indice de contamination dans l'huile. L'état de l'huile est acceptable pour la durée de service.

Depot: SCISTR
 Unique No: 5721687
 Signed: Wes Davis
 Report Date: 31 Jan 2024



GRAPHS

