LIEBHERR

CONSTRUCTION EQUIPMENT

NO UNIT 02614597 - Diesel Engine

() <1

2

ppm

ppm

Sample No: LH

Sodium

Potassium

Oil Type: SAE 10W40



VISC @ 100 C	COL	13.0	 	
Oxidation (PA)	%	63	 	
CONT	AMINATIO	ON		
Water	%	NEG	 	
Soot %	%	0	 	
Nitration (PA)	%	57	 	
Sulfation (PA)	%	55	 	
Glycol	%	NEG	 	
Fuel	%	<1.0	 	
Silicon	mag	9	 	

WEA	R META	LS		
Iron	ppm	O 5	 	
Copper	ppm	31	 	
Lead	ppm	1	 	
Tin	ppm	○ <1	 	
Aluminum	ppm	2	 	
Chromium	ppm	() <1	 	
Molybdenum	ppm	56	 	
Nickel	ppm	○ <1	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	0	 	
Vanadium	ppm	0	 	

OITIVES				
ppm	1092			
ppm	932			
ppm	1154			
ppm	984			
ppm	() <1			
ppm	3			
	ppm ppm ppm ppm	ppm	ppm	ppm





LIEBHERR CANADA LTD.

1015 SUTTON DRIVE BURLINGTON, ON CA L7L 5Z8

Contact: Joseph Rodgers joseph.rodgers@liebherr.com

T:

F: (905)319-6622

Diagnosis

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:LIEMISUnique No:5723692Signed:Kevin MarsonReport Date:12 Feb 2024

LIEBHERR





GRAPHS

