

# LIEBHERR

## CONSTRUCTION EQUIPMENT



### LIEBHERR LH60 152284 - Front Differential

Sample No: LH0284972

Oil Type: GEAR OIL SAE 80W90



**LIEBHERR CANADA LTD.**  
 1015 SUTTON DRIVE  
 BURLINGTON, ON  
 CA L7L 5Z8  
 Contact: Joseph Rodgers  
 joseph.rodgers@liebherr.com  
 T:  
 F: (905)319-6622



#### SAMPLE INFORMATION

Sample Number	LH0284972	---	---	---
Sample Date	14 Feb 2024	---	---	---
Machine Hours	596	---	---	---
Oil Hours	0	---	---	---
Oil Changed	Changed	---	---	---
Sample Status	NORMAL	---	---	---



#### OIL CONDITION

Visc @ 40°C	cSt	● 138	---	---	---
-------------	-----	-------	-----	-----	-----



#### CONTAMINATION

Water	%	NEG	---	---	---
Silicon	ppm	● 3	---	---	---
Sodium	ppm	● 3	---	---	---
Potassium	ppm	● <1	---	---	---



#### WEAR METALS

Iron	ppm	● 5	---	---	---
Copper	ppm	● 13	---	---	---
Lead	ppm	● 1	---	---	---
Tin	ppm	● 0	---	---	---
Aluminum	ppm	● <1	---	---	---
Chromium	ppm	● 0	---	---	---
Molybdenum	ppm	● 0	---	---	---
Nickel	ppm	● 0	---	---	---
Titanium	ppm	0	---	---	---
Silver	ppm	<1	---	---	---
Manganese	ppm	● 0	---	---	---
Vanadium	ppm	0	---	---	---



#### ADDITIVES

Calcium	ppm	● 7	---	---	---
Magnesium	ppm	● 1	---	---	---
Zinc	ppm	● 13	---	---	---
Phosphorus	ppm	● 1814	---	---	---
Barium	ppm	● 6	---	---	---
Boron	ppm	● 140	---	---	---

#### Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: LIEMIS  
 Unique No: 5733186  
 Signed: Wes Davis  
 Report Date: 15 Feb 2024



### GRAPHS

