## LIEBHERR

**CONSTRUCTION EQUIPMENT** 

### LIEBHERR LH40M 156305-1215 - Swing Drive

Sample No: LH0278473

Oil Type: GEAR OIL SAE 80W90



Jampio	Otatas		HOIIWAL		
	OIL CO	NDITION			
/isc @	40°C	cSt	<b>177</b>	 	

CONTAMINATION							
Water	%	NEG					
Silicon	ppm	<b>14</b>					
Sodium	ppm	<b>5</b>					
Potassium	ppm	<b>3</b>					

WEA	R METAL	S		
PQ		<b>563</b>	 	
Iron	ppm	<b>562</b>	 	
Copper	ppm	<b>175</b>	 	
Lead	ppm	<b>5</b>	 	
Tin	ppm	<b>17</b>	 	
Aluminum	ppm	<b>4</b>	 	
Chromium	ppm	<b>2</b>	 	
Molybdenum	ppm	<b>0</b>	 	
Nickel	ppm	<b>0</b> <1	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	<b>6</b>	 	
Vanadium	ppm	0	 	

ADDITIVES         Calcium       ppm       46            Magnesium       ppm       1            Zinc       ppm       27            Phosphorus       ppm       2219            Barium       ppm       11								
Magnesium         ppm         1              Zinc         ppm         27              Phosphorus         ppm         2219	ADDITIVES							
Zinc         ppm         27               Phosphorus         ppm         2219	Calcium	ppm	<b>46</b>					
Phosphorus ppm <b>2219</b>	Magnesium	ppm	<b>1</b>					
	Zinc	ppm	<b>27</b>					
Barium ppm <b>11</b>	Phosphorus	ppm	<b>2219</b>					
	Barium	ppm	<b>11</b>					
Boron ppm <b>14</b>	Boron	ppm	<b>14</b>					



Urban Mine
72 Rothwell Rd.
Winnipeg, MB
CA R3P 2H7
Contact: SERVICE

T: (204)774-0192

F:

#### Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.Metal levels are typical for a new component breaking in. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: URBWIN
Unique No: 5734614
Signed: Kevin Marson
Report Date: 23 Feb 2024

# LIEBHERR







#### **GRAPHS**

