

LIEBHERR

CONSTRUCTION EQUIPMENT



LIEBHERR LH60M 141098-1217 - Rear Differential

Sample No: LH0284995

Oil Type: GEAR OIL SAE 80W90



JOHN ZUBICK LTD.
 105 CLARKE ROAD
 LONDON, ON
 CA N5W 5C9
 Contact: John French
 honeil@zubicks.com
 T: (519)451-5470
 F: (519)451-4245



SAMPLE INFORMATION

Sample Number	LH0284995	LH0251565	LH0234953	---
Sample Date	22 Feb 2024	24 Feb 2023	14 Nov 2022	---
Machine Hours	2811	934	467	---
Oil Hours	0	0	0	---
Oil Changed	Changed	Changed	Changed	---
Sample Status	NORMAL	NORMAL	NORMAL	---



OIL CONDITION

Visc @ 40°C	cSt	108	111	180	---
-------------	-----	-----	-----	-----	-----



CONTAMINATION

Water	%	NEG	NEG	NEG	---
Silicon	ppm	3	2	2	---
Sodium	ppm	<1	<1	3	---
Potassium	ppm	<1	<1	<1	---



WEAR METALS

Iron	ppm	20	9	17	---
Copper	ppm	37	9	11	---
Lead	ppm	<1	0	<1	---
Tin	ppm	0	0	0	---
Aluminum	ppm	<1	<1	<1	---
Chromium	ppm	0	0	0	---
Molybdenum	ppm	0	<1	0	---
Nickel	ppm	0	<1	<1	---
Titanium	ppm	0	0	0	---
Silver	ppm	0	0	0	---
Manganese	ppm	0	<1	<1	---
Vanadium	ppm	0	0	0	---



ADDITIVES

Calcium	ppm	15	13	8	---
Magnesium	ppm	6	5	<1	---
Zinc	ppm	34	21	13	---
Phosphorus	ppm	1189	1283	1213	---
Barium	ppm	37	39	336	---
Boron	ppm	258	265	5	---

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: JOHLON
 Unique No: 5734845
 Signed: Wes Davis
 Report Date: 23 Feb 2024



GRAPHS

