LIEBHERR

CONSTRUCTION EQUIPMENT



Sample No: LH

Oil Type: GEAR OIL SAE 80W90

5					
SAMPLEIN	IFORMATION				
Sample Number	LH	LH			
Sample Date	04 Mar 2024	29 Jun 2023			
Machine Hours	6970	6242			
Oil Hours	135	135			
Oil Changed	Not Changd	Not Changd			
Sample Status	NORMAL	NORMAL			
OIL CONDITION					
Visc @ 40°C cSt	190	O 179			
**					
CONTAMINATION					

CONTAMINATION							
Water	%	NEG	NEG				
Silicon	ppm	0 1	O <1				
Sodium	ppm	3	3				
Potassium	ppm	1	O <1				

WEA	R METAL	S		
PQ		0 0		
Iron	ppm	615	○ 319	
Copper	ppm	24	O 17	
Lead	ppm	O <1	O <1	
Tin	ppm	0 <1	O 0	
Aluminum	ppm	() <1	O <1	
Chromium	ppm	3	O 2	
Molybdenum	ppm	0	O 0	
Nickel	ppm	 <1	O <1	
Titanium	ppm	0	0	
Silver	ppm	0	0	
Manganese	ppm	5	O 3	
Vanadium	ppm	0	0	

ADDITIVES					
Calcium	ppm	19	<u>18</u>		
Magnesium	ppm	2	O 2		
Zinc	ppm	122	O 25		
Phosphorus	ppm	2120	O 2142		
Barium	ppm	0	O 0		
Boron	ppm	8	1		



LIEBHERR CANADA LTEE 444 AVENUE DE LA FRICHE DOLBEAU-MISTASSINI, QC CA G8L 3M7

Contact: Martin Gagnon martin.gagnon@liebherr.com

F: (418)276-9844

,

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:LBADOLUnique No:5737110Signed:Kevin MarsonReport Date:06 Mar 2024

LIEBHERR







GRAPHS

