# LIEBHERR





Sample No: LH0286518

Oil Type: GEAR OIL ISO 220

5				
U SAN	<b>IPLE INFO</b>	ORMATION		
Sample Number		LH0286518	 	
Sample Date		14 Mar 2024	 	
Machine Hours		493	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
<u> </u>				
OIL	ONDITIO	ON		
/isc @ 40°C	cSt	<b>225</b>	 	
CON	TAMINA	ATION		
Water	%	NEG	 	
Silicon	ppm	<b>6</b>	 	
Sodium	ppm	<b>0</b> 1	 	
Potassium	ppm	<b>0</b> <1	 	
	R META			
lron	ppm	<b>26</b>	 	
Copper	ppm	O <1	 	
_ead	ppm	<b>0</b> 0	 	
Γin	ppm	0	 	
Aluminum	ppm	<b>2</b>	 	
Chromium	ppm	<b>O</b> <1	 	
Molybdenum	ppm	<b>0</b>	 	
Nickel	ppm	O <1	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	0	 	
/anadium	ppm	0	 	
ADD	ITIVES			
Calcium	ppm	<b>50</b>	 	
Magnesium	ppm	<b>O</b> <1	 	
Zinc	ppm	<b>25</b>	 	
Phosphorus	ppm	<b>404</b>	 	

#### LIEBHERR CANADA LTD.

1015 SUTTON DRIVE BURLINGTON, ON CA L7L 5Z8

Contact: Steve Lehto steve.lehto@liebherr.com

T: (905)319-9222 F: (905)319-6617

### Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL ISO 220. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: LIEMIS
Unique No: 5747555
Signed: Wes Davis
Report Date: 15 Mar 2024

Contact/Location: Steve Lehto - LIEMIS

**2** 

**24** 

ppm

ppm

Barium

Boron

## LIEBHERR

### CONSTRUCTION EQUIPMENT





### **GRAPHS**

