LIEBHERR

CONSTRUCTION EQUIPMENT



Sample No: LH0284809

Oil Type: PETRO CANADA SUPREME 5W30

_								
SAMPLE INFORMATION								
Sample Number		LH0284809	LH0277029					
Sample Date		02 Mar 2024	21 Oct 2023					
Machine Hours		11699	1117					
Oil Hours		0	0					
Oil Changed		N/A	Changed					
Sample Status		NORMAL	ABNORMAL					
OILC	ONDITIO	N						
			0.405					
Visc @ 100°C	cSt	11.6	12.5					
Oxidation (PA)	%	100	194					
CON.	TAMINA	TION						
Water	%	NEG	NEG					
Soot %	%	0 0	O 0					
Nitration (PA)	%	83	101					
Sulfation (PA)	%	66	104					
Glycol	%	NEG	NEG					
Fuel	%	<1.0	<1.0					
Silicon	ppm	6	O 12					
Sodium	ppm	4	3					
Potassium	ppm	1	3					

₩ WEA	R METALS			
Iron	ppm	9	O 17	
11011	ppiii	O -	0	
Copper	ppm	26	O 135	
Lead	ppm	2	O 12	
Tin	ppm	0 <1	O 1	
Aluminum	ppm	2	○ 3	
Chromium	ppm	0 <1	O 1	
Molybdenum	ppm	56	41	
Nickel	ppm	0 <1	O 0	
Titanium	ppm	0	0	
Silver	ppm	0	O <1	
Manganese	ppm	0	O 2	
Vanadium	ppm	0	0	

ADDITIVES							
Calcium	ppm	909	1414				
Magnesium	ppm	1073	○ 820				
Zinc	ppm	1143	916				
Phosphorus	ppm	975	O 758				
Barium	ppm	3	21				
Boron	ppm	27	5 4				



LIEBHERR CANADA

10 LYNDS AVENUE MONCTON, NB CA E1H 3K2

Contact: Bryan Wood bryan.wood@liebherr.com T:

F: (506)854-2940

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:LIEMONUnique No:5747765Signed:Kevin MarsonReport Date:18 Mar 2024

LIEBHERR

CONSTRUCTION EQUIPMENT





GRAPHS

