

# LIEBHERR

## CONSTRUCTION EQUIPMENT



### [(364849)] LIEBHERR R934 053396-1487 - Left Final Drive

Sample No: LH0219936

Oil Type: LIEBHERR GEAR BASIC 90 LS



#### SAMPLE INFORMATION

Sample Number	LH0219936	LH	---	---
Sample Date	15 Mar 2024	09 Feb 2022	---	---
Machine Hours	1995	0	---	---
Oil Hours	0	0	---	---
Oil Changed	Changed	Changed	---	---
Sample Status	NORMAL	NORMAL	---	---

#### HUBERT & FILS

474 ROUTE 105  
BOIS-FRANC, QC  
CA J9E 3A9

Contact: Eric Brisebois

ericbrisebois99@gmail.com

T:

F:



#### OIL CONDITION

Visc @ 40°C	cSt	89.0	● 196	---	---
-------------	-----	------	-------	-----	-----



#### CONTAMINATION

Water	%	NEG	NEG	---	---
Silicon	ppm	● 163	● 3	---	---
Sodium	ppm	● 14	● 5	---	---
Potassium	ppm	● 15	● 4	---	---



#### WEAR METALS

Iron	ppm	● 278	● 72	---	---
Copper	ppm	● <1	● <1	---	---
Lead	ppm	● 0	● <1	---	---
Tin	ppm	● 0	● 0	---	---
Aluminum	ppm	● 45	● <1	---	---
Chromium	ppm	● 4	● 1	---	---
Molybdenum	ppm	● 0	● 0	---	---
Nickel	ppm	● 4	● <1	---	---
Titanium	ppm	● 3	● <1	---	---
Silver	ppm	0	0	---	---
Manganese	ppm	● 2	● 1	---	---
Vanadium	ppm	0	0	---	---



#### ADDITIVES

Calcium	ppm	41	● 17	---	---
Magnesium	ppm	● 14	● <1	---	---
Zinc	ppm	22	● 16	---	---
Phosphorus	ppm	1065	● 1533	---	---
Barium	ppm	● 2	● 16	---	---
Boron	ppm	142	● 4	---	---

#### Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

Depot: HUBBOI

Unique No: 5750481

Signed: Wes Davis

Report Date: 28 Mar 2024



### GRAPHS

