## LIEBHERR

## **CONSTRUCTION EQUIPMENT**

### LIEBHERR LH50 138442 - Diesel Engine

Sample No: LH0286761

4

Oil Type: DIESEL ENGINE OIL SAE 30



OIL CO	ONDITION				
Visc @ 40°C	cSt		87.2		
Visc @ 100°C	cSt	<b>12.5</b>		12.4	
Oxidation (PA)	%	82		76	

CONTAMINATION						
Water	%	NEG	NEG	NEG		
Soot %	%	<b>0</b>		0		
Nitration (PA)	%	81		72		
Sulfation (PA)	%	57		57		
Glycol	%	NEG	NEG	NEG		
Fuel	%	<1.0	<1.0	<1.0		
Silicon	ppm	<b>4</b>	<b>6</b>	<b>7</b>		
Sodium	ppm	<b>1</b>	O 1	O 2		
Potassium	ppm	<b>1</b>	0 6	O 3		

(O) NAVE A					
WEA	R METALS				
Iron	ppm	<b>4</b>	<b>3</b>	O 5	
Copper	ppm	<b>2</b>	O 2	O 2	
Lead	ppm	<b>0</b>	O <1	O 1	
Tin	ppm	<b>0</b>	O 0	O 0	
Aluminum	ppm	<b>2</b>	O 2	O 2	
Chromium	ppm	<b>0</b> <1	O 0	O <1	
Molybdenum	ppm	<b>49</b>	<b>58</b>	<b>58</b>	
Nickel	ppm	<b>0</b>	O <1	O <1	
Titanium	ppm	<b>()</b> <1	<b>0</b>	O 0	
Silver	ppm	<b>0</b>	O 0	O <1	
Manganese	ppm	<b>0</b>	O 0	O 0	
Vanadium	ppm	0	0	0	

ADI	DITIVES				
	DIIIAE2				
Calcium	ppm	<b>1119</b>	O 1114	1157	
Magnesium	ppm	<b>892</b>	O 944	950	
Zinc	ppm	<b>1152</b>	1188	O 1218	
Phosphorus	ppm	<b>940</b>	O 1008	<b>977</b>	
Barium	ppm	<b>○</b> <1	0	O <1	
Boron	ppm	<b>23</b>	<b>3</b>	O 2	



**LIEBHERR CANADA LTD.** 1015 SUTTON DRIVE BURLINGTON, ON

CA L7L 5Z8

Contact: Joseph Rodgers joseph.rodgers@liebherr.com

T:

F: (905)319-6622

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot: LIEMIS
Unique No: 5759166
Signed: Wes Davis
Report Date: 02 Apr 2024

# LIEBHERR





#### **GRAPHS**

