LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH50 137429 - Splitter Box

Sample No: LH0286798

Oil Type: GEAR OIL SAE 75W90



OIL C	ONDITIO	ON				
Visc @ 40°C	cSt	○ 85.0	○ 85.4	85.4	88.9	

CONTAMINATION						
Water	%	NEG	NEG	NEG	NEG	
Silicon	ppm	1	O 1	02	O 2	
Sodium	ppm	 <1	O <1	O <1	O <1	
Potassium	ppm	0 <1	O <1	O 0	O <1	

(O) WEA					
WEA	R METAL	5			
Iron	ppm	11	9	0 8	O 14
Copper	ppm	 <1	O <1	O <1	O <1
Lead	ppm	0	0	O 0	O 2
Tin	ppm	0	0	O 0	O 0
Aluminum	ppm	 <1	O <1	<1	O <1
Chromium	ppm	0	0	O 0	O <1
Molybdenum	ppm	0	0	O 0	O 0
Nickel	ppm	0	0	O <1	O <1
Titanium	ppm	0	0	0	0
Silver	ppm	0	0	<1	<1
Manganese	ppm	0	O 0	O 0	O 0
Vanadium	ppm	0	0	0	0

variadium	ppm	U	U	U	U
ADDI	TIVES				
Calcium	ppm	32	○ 31	31	30
Magnesium	ppm	2	0 2	0 1	O 2
Zinc	ppm	113	O 103	93	48
Phosphorus	ppm	1135	O 1195	1136	1350
Barium	ppm	0	0	O <1	0
Boron	ppm	262	O 277	284	308



CMI - COMBINED METAL INDUSTRIES 505 GARY RAY DRIVE NORTH YORK, ON CA M9L 1P9 Contact: Greg Sacher gsacher@combinedmetal.com T: (416)642-7262 F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:COMWESUnique No:5759300Signed:Wes DavisReport Date:02 Apr 2024

CONSTRUCTION EQUIPMENT





GRAPHS

