# LIEBHERR





Sample No: LH0289455

Oil Type: PETRO CANADA TRAXON 75W90 SYNTHETIC

Sam	ple Infor	mation		
Sample Number		LH0289455	LH0242622	 
Sample Date		04 Apr 2024	17 Oct 2022	 
Machine Hours		1873	325	 
Oil Hours		0	0	 
Oil Changed		Changed	Changed	 
Sample Status		NORMAL	SEVERE	 
Nample Otatus		HOTHWIAL	OLVLITE	
Oil	ondition	ı		
Visc @ 40°C	cSt	<b>103</b>	O 188	 
V130 @ 40 0	001	0 100	0 100	
Conf	aminati	on		
Water	%	NEG	NEG	 
Silicon	ppm	<1	4	 
Sodium	ppm	<b>1</b>	<b>4</b>	 
Potassium	ppm	O <1	02	 
<b>Wed</b>	ır Metals	<b>.</b>		
PQ			O 611	 
Iron	ppm	<b>171</b>	926	 
Copper	ppm	2	1	 
Lead	ppm	0	0	 
Tin		0	0	 
Aluminum	ppm	<1	1	
Chromium	ppm	<b>2</b>	0 14	 
	ppm		_	
Molybdenum	ppm	0 0	0 <1	 
Nickel	ppm	<b>0</b> <1	02	 
Titanium	ppm	0	<1	 
Silver	ppm	0	0	 
Manganese	ppm	01	0 7	 
Vanadium	ppm	0	0	 
Add				
Add	itives			
Calcium	ppm	<b>10</b>	O 14	 
Magnesium	ppm	0 2	0 <1	 
Zinc	ppm	19	O 18	 
Phosphorus		① 1145	831	 
Barium	ppm	O <1	031	 
	ppm			
Boron	ppm	<b>252</b>	3	 

#### LIEBHERR CANADA LTD.

1015 SUTTON DRIVE BURLINGTON, ON CA L7L 5Z8

Contact: Steve Lehto steve.lehto@liebherr.com

T: (905)319-9222 F: (905)319-6617

#### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:LIEMISUnique No:5760866Signed:Wes DavisReport Date:09 Apr 2024

Contact/Location: Steve Lehto - LIEMIS

## LIEBHERR

CONSTRUCTION EQUIPMENT





### **Graphs**

