LIEBHERR

CONSTRUCTION EQUIPMENT

LIEBHERR LH30M 090077 - Rear Differential

Sample No: LH0276287

Oil Type: GEAR OIL SAE 75W90



Sample Status		NORMAL	NORMAL	
Oil Cor	ndition			
Visc @ 40°C	cSt	103	O 102	

Cont	aminatio	n			
Water	%	NEG	NEG	 	
Silicon	ppm	0	O <1	 	
Sodium	ppm	1	O 1	 	
Potassium	ppm	0	O <1	 	

Wear Metals Iron ppm 2 5 Copper ppm <1 2 Lead ppm 0 <1 Tin ppm 0 <1 Aluminum ppm 0 0 Chromium ppm 0 0 Molybdenum ppm 0 <1 Nickel ppm 0 <1	
Copper ppm 0 Nickel ppm 0 0 0	
Lead ppm 0 <1 Tin ppm 0 <1 Aluminum ppm 0 0 Chromium ppm 0 0 Molybdenum ppm 0 <1 Nickel ppm 0 <1	
Tin ppm 0 Aluminum ppm 0 0 Chromium ppm 0 0 Molybdenum ppm 0 <1	
Aluminum ppm 0 0 Chromium ppm 0 0 Molybdenum ppm 0 <1	
Chromium ppm ○ 0 ○ Molybdenum ppm ○ 0 <1	
Molybdenum ppm ○ 0 <1 Nickel ppm ○ 0 <1	
Nickel ppm 0 0	
Titanium ppm 0	
Silver ppm 0 <1	
Manganese ppm	
Vanadium ppm 0	

Addi	itives			
Calcium	ppm	16	O 44	
Magnesium	ppm	3	O 2	
Zinc	ppm	11	O 10	
Phosphorus	ppm	1199	O 1348	
Barium	ppm	0	O 0	
Boron	ppm	315	○ 323	



ELG Canada 4375 CORPORATE DRIVE BURLINGTON, ON CA L7L 5P7 Contact: Service Manager

T

F: (905)335-9687

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:STR437BURUnique No:5762920Signed:Wes DavisReport Date:18 Apr 2024

Submitted By: Rick Cule

LIEBHERR







Graphs

