LIEBHERR

CONSTRUCTION EQUIPMENT



Sample No: LH0289695

Potassium

Oil Type: GEAR OIL SAE 75W90

ppm

_						
Samp	le Informa	ation				
Sample Number		LH0289695	LH0247149	LH0256691	LH0251650	
Sample Date		16 Apr 2024	26 Jun 2023	02 Apr 2023	06 Feb 2023	
Machine Hours		13245	10141	9107	8526	
Oil Hours		0	0	0	0	
Oil Changed		Changed	Changed	N/A	Changed	
Sample Status		NORMAL	NORMAL	NORMAL	NORMAL	
Oil Co	ndition					
Visc @ 40°C	cSt	107	O 103	O 101	99.2	
Contamination						
Water	%	NEG	NEG	NEG	NEG	
Silicon	ppm	0 <1	O 2	3	3	
Sodium	ppm	2	O <1	O <1	O <1	

0

				0	J
Wear	Metals				
Iron	ppm	0 <1	○ 36	47	O 44
Copper	ppm	2	5	7	9
Lead	ppm	0	O 0	O 1	O <1
Tin	ppm	0	O 0	O 0	O 0
Aluminum	ppm	0	O <1	O <1	O <1
Chromium	ppm	0	O 0	0	O 0
Molybdenum	ppm	0	O 0	0	O 0
Nickel	ppm	0	O 0	0	O 0
Titanium	ppm	0	O 0	O 0	O 0
Silver	ppm	0	0	0	0
Manganese	ppm	0	O <1	O <1	O <1
Vanadium	ppm	0	0	0	0

variadium	ppm	U	U	U	U
Addit	lives				
Calcium	ppm	13	O 5	0 8	O 11
Magnesium	ppm	 <1	O 1	2	0 2
Zinc	ppm	11	O 12	1 3	18
Phosphorus	ppm	1233	O 1299	1304	O 1363
Barium	ppm	0	0	O 0	0
Boron	ppm	315	○ 301	○ 309	○ 319



RAM IRON AND METAL

60 Ashwarren Road TORONTO, ON CA M3J 1Z5

Contact: PETER RACCO PETER@RAMIRON.COM T: (416)630-4545

F: (416)630-4545

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:RAMTORUnique No:5762928Signed:Wes DavisReport Date:17 Apr 2024

LIEBHERR

CONSTRUCTION EQUIPMENT





Graphs

