# LIEBHERR





Sample No: LH0288019

Oil Type: PETRO CANADA TRAXON 75W90 SYNTHETIC

<b>5</b>					
Sam	ple Info	rmation			
Sample Number		LH0288019	LH0240697		
Sample Date		08 May 2024	19 Oct 2022		
Machine Hours		24317	21820		
Oil Hours		0	0		
Oil Changed		Changed	Changed		
Sample Status		NORMAL	NORMAL		
Oil C	ondition	1			
Visc @ 40°C	cSt	155	86.9		
Contamination					

Conte	amination			
Water	%	NEG	NEG	 
Silicon	ppm	<b>5</b>	O 13	 
Sodium	ppm	<b>3</b>	<b>4</b>	 
Potassium	ppm	<b></b> <1	O <1	 

Iron   ppm	(Ö)				
Copper         ppm         2         4             Lead         ppm         0         0             Tin         ppm         0         <1             Aluminum         ppm         <1         <1             Chromium         ppm         0         <1             Molybdenum         ppm         0         <1             Nickel         ppm         0         0             Titanium         ppm         0         0             Silver         ppm         0         0             Manganese         ppm         2         <1	Wed	ar Metals			
Lead         ppm         0         0             Tin         ppm         0         <1             Aluminum         ppm         <1         <1             Chromium         ppm         0         <1             Molybdenum         ppm         0         <1             Nickel         ppm         0         0             Titanium         ppm         0         0             Silver         ppm         0         0             Manganese         ppm         2         <1	Iron	ppm	<b>223</b>	<b>6</b> 1	 
Tin         ppm         0         <1	Copper	ppm	<b>2</b>	O 4	 
Aluminum       ppm       <1	Lead	ppm	<b>0</b>	O 0	 
Chromium         ppm         1         0             Molybdenum         ppm         0         <1	Tin	ppm	<b>0</b>	O <1	 
Molybdenum         ppm         0              Nickel         ppm         0         0             Titanium         ppm         0         0             Silver         ppm         0         0             Manganese         ppm         2         <1	Aluminum	ppm	<b></b> <1	O <1	 
Nickel         ppm         0         0             Titanium         ppm         0         0             Silver         ppm         0         0             Manganese         ppm         2         <1	Chromium	ppm	<b>1</b>	O 0	 
Titanium         ppm         0         0             Silver         ppm         0         0             Manganese         ppm         2         <1	Molybdenum	ppm	<b>0</b>	O <1	 
Silver         ppm         0         0             Manganese         ppm         2         <1	Nickel	ppm	<b>0</b>	O 0	 
Manganese ppm <b>2</b>	Titanium	ppm	<b>0</b>	O 0	 
	Silver	ppm	0	0	 
Voice allows	Manganese	ppm	<b>2</b>	O <1	 
vanadium ppm 0	Vanadium	ppm	0	0	 

vanadium	ppm	U	0	 
Addit	livos			
	IVES			
Calcium	ppm	28	40	 
Magnesium	ppm	<b>2</b>	O 2	 
Zinc	ppm	<b>9</b>	25	 
Phosphorus	ppm	2074	1272	 
Barium	ppm	<b>4</b>	O <1	 
Boron	ppm	50	284	 



## West Coast Metal Recycling

5771 Production Way Langley, BC CA V3A 4N5 Contact: Terry . terry@gotmetal.ca

T: F:

#### Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill.
Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

Depot:WES577LANUnique No:5775852Signed:Wes DavisReport Date:10 May 2024

Contact/Location: Terry . - WES577LAN







### **Graphs**

