LIEBHERR

CONSTRUCTION EQUIPMENT



Sample No: LH

Oil Type: GEAR OIL SAE 80W90

Sample Information							
Sample Number	LH	LH	LH	LH0250096			
Sample Date	17 Jun 2024	15 Feb 2024	12 Sep 2023	27 Mar 2023			
Machine Hours	5960	5100	4000	2020			
Oil Hours	0	0	0	0			
Oil Changed	Changed	Changed	Changed	N/A			
Sample Status	NORMAL	NORMAL	NORMAL	NORMAL			
A							

Campio Clarac		HOIMAL	14011111111	1401111111	14011111111
Oil Co	ndition				
Visc @ 40°C	cSt	178		O 174	

Conto	ımination				
Water	%	NEG	NEG	NEG	NEG
Silicon	ppm	6	O 11	1 3	12
Sodium	ppm	6	9	O 15	12
Potassium	ppm	1	02	02	01

Wear Metals						
Iron	ppm	22	35	40	3 5	
Copper	ppm	2	3	4	4	
Lead	ppm	0	0	O 0	O <1	
Tin	ppm	0	O 0	O 0	0	
Aluminum	ppm	() <1	1	O 2	1	
Chromium	ppm	0	O 0	O 0	0	
Molybdenum	ppm	0	0	<1	O <1	
Nickel	ppm	O <1	O <1	 <1	O <1	
Titanium	ppm	0	0	0	<1	
Silver	ppm	0	0	0	<1	
Manganese	ppm	() <1	<1 <1	O 2	O 2	
Vanadium	ppm	0	0	0	0	

vanadium	ppm	U	U	U	U	
6						
Additives						
Calcium	ppm	31	47	87	108	
Magnesium	ppm	2	O 2	O 2	O 1	
Zinc	ppm	23	29	42	○ 38	
Phosphorus	ppm	2321	O 2274	O 2371	O 2438	
Barium	ppm	0	O 0	O 0	0	
Boron	ppm	1	O 1	3	3	



Industrial Metals 550 Messier St. Winnipeg, MB CA R2J 0G5

Contact: Service Manager

T: F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:IND550WINUnique No:5800549Signed:Wes DavisReport Date:19 Jun 2024

CONSTRUCTION EQUIPMENT





Graphs

